WEVER & DUCRÉ LIGHTING

DEEPER 1.0 PAR16

152120B0C

PROJECT

TYPE


NOTES

QUANTITY

DATE



Round ceiling recessed downlight made from die-cast aluminium; surface Black Matt; powder coated, matt texture; RAL 9011; installation without tools using wire springs; suitable for ceiling thickness of 4-38 mm; recessed depth 120mm; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; degree of protection IP20; Class 2; lamp not included;



LUMINAIRE

Ceiling
Recessed
Black Matt
RAL 9011 [a]
IP20
Interior

LAMP

lamp PAR16
socket GU10
max. per socket 12.0 W
CRI ≥ 90

OPTICAL

UGR ≤ 16

ELECTRICAL

100 - 240 V
Class II

PHYSICAL

diameter 84 mm
height 112 mm
0.15 kg
blade springs

CUTOUT

diameter 76-79 mm
min. ceiling thickness 4 mm
max. ceiling thickness 38 mm
recessed depth 120 mm


[a] Colour may deviate slightly due to production conditions


MEASURED LAMPS

PAR16 LAMP 3000K CRI90
455 lm

PAR16 LAMP 2700K CRI90
440 lm

LIGHT DISTRIBUTION





DEEPER 1.0 PAR16

152120B0C

ELECTRICAL ACCESSORIES

LED LAMPS

TYPE	COLOUR	VOLTAGE	ITEM NUMBER
	Black Texture		W901228B3
	Black Texture		W901228B5

LAMPS

PAR16 LED LAMP

TYPE	COLOUR	VOLTAGE	Ø·H (MM)	ITEM NUMBER
2700K | >90 CRI | GU10 | 220-240VAC	White		50·60	901228W3
3000K | >90 CRI | GU10 | 220-240VAC	White		50·60	901228W5
2700K | >80 CRI | GU10 | 220-240VAC	Silver		50·55	905227S2
3000K | >80 CRI | GU10 | 220-240VAC	Silver		50·55	905227S4

['152120B0C'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com