WEVER & DUCRÉ LIGHTING

MATCH SNEAK trimless 1.0

190451B3

PROJECT


TYPE

NOTES


QUANTITY

DATE





Ceiling recessed spotlight made from die-cast aluminium with round base; for trimless installation; surface Black Matt; powder coated; matt texture; RAL 9011; installation without tools using wire springs; suitable for ceiling thickness of 12.5/15/20/25 mm; recessed depth 53mm; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; ≤ 2 SDCM (initial MacAdam); CRI ≥ 90; beam angle 30°; spotlight head 350° rotatable and 55° tiltable; degree of protection IP20; Class 3; IC rated; driver not included; to be combined with the plasterkit suitable for ceiling thickness; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Ceiling
Semi-Recessed
tilt max 55 °
rotation 350 °
Black Matt
RAL 9011 [a]
IP20
IC rated
Interior
535 lm

LED MODULE

2700 K
CRI ≥ 90
L80 / 50000h
≤ 2 SDCM (initial MacAdam)

OPTICAL

Medium (standard)
beam angle 30°
CIE flux code: 97 100 100 100 100

ELECTRICAL

excl. driver
17 V
Class III

PHYSICAL


diameter 26 mm
height 117 mm
0.15 kg

CUTOUT

diameter 78-80 mm
min. ceiling thickness 12.5 mm
max. ceiling thickness 25 mm
recessed depth 53 mm

[a] Colour may deviate slightly due to production conditions

LIGHT DISTRIBUTION



MATCH SNEAK trimless 1.0

190451B3

CONE DIAGRAM

medium (standard) 30°

h (m)	E0° (lx)	ø (m)
1	1590	0.53
2	400	1.07
3	180	1.60
4	100	2.14
5	60	2.67

Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.99	0.98	0.97	0.96	0.95
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF[a]	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF[a]	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

[a]According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

ELECTRICAL ACCESSORIES

DRIVER

TYPE	COLOUR	VOLTAGE	L·W·H (MM)	ITEM NUMBER
6.3W | 350mA | 8.6-18V | 100-240VAC		8.6-18V	66·39·22	90213303
7W | 350mA | 12-21V | phase-cut dim | 220-240VAC		12-21V	68·33·22	90223301
14W | 350mA | 10-40V | DALI-2 push dim | 220-240VAC		10-40V	166·29·21	90243502

MOUNTING ACCESSORIES

PLASTERKIT

TYPE	COLOUR	VOLTAGE	Ø·H (MM)	ITEM NUMBER
			73·29	90017210

['190451B3'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com