WEVER & DUCRÉ LIGHTING

RONY ADJUST petit 1.0

110441B3C

PROJECT

TYPE


NOTES

QUANTITY

DATE



Round ceiling recessed luminaire made from aluminium; surface Black Matt; powder coated, matt texture; RAL 9011; installation without tools using blade springs; recessed depth 63mm; with COB (Chip on Board) technology for maximum efficiency; 350mA; light colour 2700 K; ≤ 2 SDCM (initial MacAdam); CRI ≥ 90; beam angle 15°; 355° rotatable and 35° tiltable; degree of protection IP20; Class 3; driver not included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Ceiling
Recessed
tilt max 35 °
rotation 355 °
Black Matt
RAL 9011 [a]
IP20
IC rated
Interior
535 lm / 350mA

LED MODULE

2700 K
CRI ≥ 90
L70 / 50000h
≤ 2 SDCM (initial MacAdam)
650 lm / 350mA
109 lm/W [b]
6 W [b]

OPTICAL

Narrow
beam angle 15°
CIE flux code: 98 100 100 100 100

ELECTRICAL

excl. driver
17 V
Class III


PHYSICAL

diameter 80 mm
height 58 mm
0.12 kg
blade springs

CUTOUT

diameter 70-73 mm
min. ceiling thickness 8 mm
recessed depth 63 mm

LIGHT DISTRIBUTION



[a] Colour may deviate slightly due to production conditions
[b] Without electrical and optical losses

RONY ADJUST petit 1.0

110441B3C

CONE DIAGRAM

narrow 17° 350mA

h (m)	E0° (lx)	ø (m)
1	4270	0.31
2	1070	0.62
3	470	0.92
4	270	1.23
5	170	1.54

Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.99	0.98	0.97	0.96	0.95
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF[a]	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF[a]	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

[a]According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

ELECTRICAL ACCESSORIES

DRIVER

TYPE	COLOUR	VOLTAGE	L·W·H (MM)	ITEM NUMBER
6.3W | 350mA | 8.6-18V | 100-240VAC		8.6-18V	66·39·22	90213303
10W | 350mA | 13-26V | phase-cut dim | 220-240VAC		13-26V	115·41·25	90223406
14W | 350mA | 10-40V | DALI-2 push dim | 220-240VAC		10-40V	166·29·21	90243502

['110441B3C'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com