



PROJECT

TYPE


NOTES

QUANTITY

DATE



Round ceiling recessed downlight made from die-cast aluminium; adjustable; with trim; surface Black Matt; powder coated; matt texture; No matching RAL; inner ring black; installation without tools using blade springs; suitable for ceiling thickness of min. 2 mm; recessed depth 60mm; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; CRI ≥ 90 ; beam angle 31°; 360° rotatable and 35° tiltable; degree of protection IP20; Class 3; driver not included; optional honeycomb louver available, to reduce glare; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Ceiling
Recessed
tilt max 35 °
rotation 360 °
Black Matt
No matching RAL
IP20
Interior
425 lm

LED MODULE

2700 K
CRI ≥ 90
L80 / 50000h
 ≤ 2 SDCM (initial MacAdam)

OPTICAL

beam angle 31°

ELECTRICAL

excl. driver
16.7 V
system 4.2 W
Class III

PHYSICAL

diameter 76 mm
height 35 mm
0.12 kg
blade springs

CUTOUT

diameter 68-70 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 60 mm


ELECTRICAL ACCESSORIES

DRIVER TYPE	COLOUR	VOLTAGE	L·W·H (MM)	ITEM NUMBER
6W 250mA 8.6-24V 100-240VAC		8.6-24V	55·39·22	90216201
5W 250mA 12-21V phase-cut dim 220-240VAC		12-21V	68·33·22	90226201
10W 250mA 16-40V phase cut TE IP65 110-240VAC		16-40V	44·27·20	90226404
10W 250mA 10-40V DALI-2 push dim 220-240VAC		10-40V	166·29·21	90246403

OPTICAL ACCESSORIES

HONEYCOMB LOUVRE TYPE	COLOUR	VOLTAGE	Ø (MM)	ITEM NUMBER
BLIEK petit CENO LECA PIRRO QITO 1.0	Black		29	915230B0