




PROJECT

TYPE


NOTES

QUANTITY

DATE



Round ceiling recessed downlight made from ASA; surface Black; No matching RAL; adjustable; 3D printed by IQ LUX; surface variations may appear due to production method; installation without tools using blade springs; suitable for ceiling thickness of min. 8 mm; recessed depth 87mm; beam angle 18°; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; CRI ≥ 90; degree of protection IP20; Class 3; driver not included;



LUMINAIRE

Ceiling
Recessed
tilt max 25 °
rotation 360 °
Black
No matching RAL
IP20
Interior
360 lm

LED MODULE

2700 K
CRI ≥ 90
L80 / 80000h
≤ 3 SDCM (initial MacAdam)

OPTICAL

Narrow
beam angle 18°

ELECTRICAL

excl. driver
18 V
system 3.0 W
Class III

PHYSICAL

diameter 81 mm
height 61 mm
0.06 kg
blade springs

CUTOUT

diameter 74-76 mm
min. ceiling thickness 8 mm
recessed depth 87 mm



ELECTRICAL ACCESSORIES

DRIVER TYPE	COLOUR	VOLTAGE	L·W·H (MM)	ITEM NUMBER
10W 200mA 30-42V phase-cut dim 220-240VAC		30-42V	85·22·41	90226402
8W 200mA 10-40V DALI-2 push dim 220-240VAC		10-40V	166·29·21	90246302

[199241B3] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducre BV apply.
© Wever & Ducre BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com