




PROJECT

TYPE


NOTES

QUANTITY

DATE



Squared ceiling recessed luminaire made from aluminium; surface Black Matt; powder coated, matt texture; RAL 9011; recessed depth 125mm; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; 355° rotatable and 35° tiltable; degree of protection IP20; Class 2; lamp not included;



LUMINAIRE

Ceiling
Recessed
tilt max 35 °
rotation 355 °
Black Matt
RAL 9011^a
IP20
Interior

LAMP

lamp PAR16
socket GU10
max. per socket 12.0 W
CRI ≥ 90

ELECTRICAL

100 - 240 V
Class II

PHYSICAL

length 70 mm
width 70 mm
height 120 mm
0.41 kg
alu plasterkit

CUTOUT



length 86 mm
width 86 mm
min. ceiling thickness 7 mm
max. ceiling thickness 32 mm
recessed depth 125 mm

MEASURED LAMPS

PAR16 LAMP 2700K CRI90
425 lm

PAR16 LAMP 3000K CRI90
445 lm

LIGHT DISTRIBUTION



^a Colour may deviate slightly due to production conditions



OTHER ACCESSORIES

METAL SPRING CLIP

TYPE	COLOUR	VOLTAGE	Ø (MM)	ITEM NUMBER
LED modules PAR16			59	90019700

SPRING CLIP

TYPE	COLOUR	VOLTAGE	Ø (MM)	ITEM NUMBER
LED Modules PAR16 max. 12W	Black		59	900198B0
LED Modules PAR16 max. 12W	Champagne		59	900198M0
LED Modules PAR16 max. 12W	White		59	900198W0

ELECTRICAL ACCESSORIES

LED LAMPS

TYPE	COLOUR	VOLTAGE	ITEM NUMBER
	Black Texture		W901228B3
	Black Texture		W901228B5

LAMPS

PAR16 LED LAMP

TYPE	COLOUR	VOLTAGE	Ø·H (MM)	ITEM NUMBER
2700K >90 CRI GU10 220-240VAC	White		50-60	901228W3
3000K >90 CRI GU10 220-240VAC	White		50-60	901228W5
2700K >80 CRI GU10 220-240VAC	Silver		50-55	905227S2
3000K >80 CRI GU10 220-240VAC	Silver		50-55	905227S4

MOUNTING ACCESSORIES

PLASTERKIT

TYPE	COLOUR	VOLTAGE	L·W·H (MM)	ITEM NUMBER
STRANGE 1.0 SNEAK TRIMLESS 1.0			81-81-42	90017120