




PROJECT

TYPE


NOTES

QUANTITY

DATE



Round ceiling recessed downlight made from die-cast aluminium; surface Black Matt; powder coated, matt texture; RAL 9011; installation without tools using blade springs; suitable for ceiling thickness of min. 10 mm; recessed depth 115mm; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; degree of protection IP20; Class 2; lamp not included;



LUMINAIRE

Ceiling
Recessed
Black Matt
RAL 9011 ^a
IP20
Interior

LAMP

lamp PAR16
socket GU10
max. per socket 12.0 W
CRI ≥ 90

OPTICAL

UGR ≤ 16

ELECTRICAL

100 - 240 V
Class II

PHYSICAL

diameter 84 mm
height 108 mm
0.12 kg
blade springs

CUTOUT



diameter 76-79 mm
min. ceiling thickness 10 mm
recessed depth 115 mm

MEASURED LAMPS

PAR16 LAMP 3000K CRI90
465 lm

PAR16 LAMP 2700K CRI90
445 lm

LIGHT DISTRIBUTION



^a Colour may deviate slightly due to production conditions



ELECTRICAL ACCESSORIES

LED LAMPS

TYPE	COLOUR	VOLTAGE	ITEM NUMBER
	Black Texture		W901228B3
	Black Texture		W901228B5

LAMPS

PAR16 LED LAMP

TYPE	COLOUR	VOLTAGE	Ø-H (MM)	ITEM NUMBER
2700K >90 CRI GU10 220-240VAC	White		50-60	901228W3
3000K >90 CRI GU10 220-240VAC	White		50-60	901228W5
2700K >80 CRI GU10 220-240VAC	Silver		50-55	905227S2
3000K >80 CRI GU10 220-240VAC	Silver		50-55	905227S4