




PROJECT

TYPE


NOTES

QUANTITY

DATE



Pendant rod suspension made from aluminium; can be cut and adjusted as desired max. 600 mm; for trimless installation; surface Black Matt; powder coated, matt texture; RAL 9011; suitable for ceiling thickness of 4-26 mm; recessed depth 85mm; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; CRI ≥ 90 ; beam angle 30°; spotlight head 360° rotatable and 90° tiltable; degree of protection IP20; Class 3; IC rated; driver not included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Ceiling
Semi-Recessed
tilt max 90 °
rotation 360 °
Black Matt
RAL 9011 ^a
IP20
IC rated
Interior
525 lm

LED MODULE

2700 K
CRI ≥ 90
L80 / 50000h
 ≤ 2 SDCM (initial MacAdam)

OPTICAL

Medium (standard)
beam angle 30°
CIE flux code: 97 100 100 100
100

ELECTRICAL

excl. driver
18 V
Class III

PHYSICAL


diameter 26 mm
height 117 mm
0.42 kg

CUTOUT

diameter 45-47 mm
min. ceiling thickness 4 mm
max. ceiling thickness 26 mm
recessed depth 85 mm

^a Colour may deviate slightly due to production conditions

LIGHT DISTRIBUTION





CONE DIAGRAM

medium (standard) ~~350~~350mA

h (m)	E0° (lx)	ø (m)
1	1530	0.54
2	380	1.09
3	170	1.63
4	100	2.18
5	60	2.72

OTHER ACCESSORIES

DRILLING TOOL

TYPE	COLOUR	VOLTAGE	Ø (MM)	ITEM NUMBER
for easy plaster finish			46	90019300

ELECTRICAL ACCESSORIES

DRIVER

TYPE	COLOUR	VOLTAGE	L·W·H (MM)	ITEM NUMBER
6.3W 350mA 8.6-18V 100-240VAC		8.6-18V	66-39-22	90213303
7W 350mA 12-21V phase-cut dim 220-240VAC		12-21V	68-33-22	90223301
8W 350mA 12-24V phase cut TE IP65 110-277VAC		12-24V	44-27-20	90223303
14W 350mA 10-40V DALI-2 push dim 220-240VAC		10-40V	166-29-21	90243502