



PROJECT

TYPE


NOTES

QUANTITY

DATE



Rectangular ceiling recessed downlight made from die-cast aluminium; surface Black Matt; RAL 9011; installation without tools using wire springs; suitable for ceiling thickness of 4-25 mm; recessed depth 60mm; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90 ; beam angle 28°; degree of protection IP20; Class 3; IC rated; driver not included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Ceiling
Recessed
Black Matt
RAL 9011^a
IP20
IC rated
Interior
560 / 580 lm

LED MODULE

2700 K
CRI ≥ 90
L80 / 50000h
 ≤ 3 SDCM (initial MacAdam)

OPTICAL

Medium (standard)
beam angle 28°
CIE flux code: 98 100 100 100 100

ELECTRICAL

excl. driver
24 V
Class III

PHYSICAL


length 119 mm
width 40 mm
height 40 mm
0.1 kg
wire springs

CUTOUT

length 116 mm
width 33 mm
min. ceiling thickness 4 mm
max. ceiling thickness 25 mm
recessed depth 60 mm

^a Colour may deviate slightly due to production conditions

LIGHT DISTRIBUTION





CONE DIAGRAM

medium (standard) **250mA**

h (m)	E0° (lx)	ø (m)
1	2250	0.45
2	560	0.90
3	250	1.35
4	140	1.81
5	90	2.26

ELECTRICAL ACCESSORIES

DRIVER TYPE	COLOUR	VOLTAGE	L·W·H (MM)	ITEM NUMBER
8.2W 300mA 14-27.5V 100-277VAC		14-27.5V	60·400·24	90219301
10W 350mA 13-26V phase-cut dim 220-240VAC		13-26V	115·41·25	90223406
12W 300mA 16-40V phase cut TE IP65 110-240VAC		16-40V	44·27·20	90229401
14W 350mA 10-40V DALI-2 push dim 220-240VAC		10-40V	166·29·21	90243502