



PROJET

MODÈLE


NOTES

QUANTITÉ

DATE



Luminaire suspendu en aluminium ; surface en Noir mat + Aluminium brossé peinture humide ; structure de surface mate ; RAL 9011 + No matching RAL ; avec suspension de câble réglable max. 4000 mm en noir de sécurité ; culot GU10 ; type de lampe PAR16 ; max. 12W; 18 V ; indice de protection IP20 ; Classe 3 ; cache-piton non inclus ;



LUMINAIRE

Plafond
Suspendu
Noir mat + Aluminium brossé
RAL 9011 + No matching RAL ^a
IP20
Intérieur
480 lm

LED MODULE

3000 K
CRI ≥ 90
L70 / 55000h
≤ 2 SDCM (initial MacAdam)

OPTIQUE

angle de faisceau 32°

ÉLECTRIQUE

sans driver
18 V
système 7.0 W
Classe 3

PHYSIQUE

diamètre 191 mm
hauteur 150 mm
0.37 kg
longueur du câble max. 2500 mm

^a Les couleurs peuvent varier légèrement en fonction des conditions de production.



ACCESSOIRES DE MONTAGE

AL | SINGLE BASE ROUND

MODÈLE	COLORIS	TENSION	Ø-H (MM)	RÉFÉRENCE ARTICLE
phase-cut dim incl. driver 220-240VAC	Noir		83-39	914112B0
phase-cut dim incl. driver 220-240VAC	Doré		83-39	914112G0
phase-cut dim incl. driver 220-240VAC	aluminium		83-39	914112L0
phase-cut dim incl. driver 220-240VAC	Champagne		83-39	914112M0
phase-cut dim incl. driver 220-240VAC	Bronze		83-39	914112Q0
phase-cut dim incl. driver 220-240VAC	Blanc		83-39	914112W0
phase cut TE incl. driver 110-277VAC	Noir		83-39	L914112B0
phase cut TE incl. driver 110-277VAC	Doré		83-39	L914112G0
phase cut TE incl. driver 110-277VAC	aluminium		83-39	L914112L0
phase cut TE incl. driver 110-277VAC	Champagne		83-39	L914112M0
phase cut TE incl. driver 110-277VAC	Bronze		83-39	L914112Q0
phase cut TE incl. driver 110-277VAC	Blanc		83-39	L914112W0

BL | SEMI RECESSED SINGLE BASE ROUND

MODÈLE	COLORIS	TENSION	Ø-H (MM)	RÉFÉRENCE ARTICLE
incl. driver 220-240VAC	Noir		84-72	914152B0
incl. driver 220-240VAC	aluminium		83-72	914152L0
incl. driver 220-240VAC	Champagne		83-72	914152M0
incl. driver 220-240VAC	Bronze		83-72	914152Q0
incl. driver 220-240VAC	Blanc		84-72	914152W0
phase cut TE incl. driver 110-277VAC	Noir		83-72	L914152B0
phase cut TE incl. driver 110-277VAC	aluminium		83-72	L914152L0
phase cut TE incl. driver 110-277VAC	Champagne		83-72	L914152M0
phase cut TE incl. driver 110-277VAC	Bronze		83-72	L914152Q0
phase cut TE incl. driver 110-277VAC	Blanc		83-72	L914152W0

EL | MULTI BASE LINEAR

MODÈLE	COLORIS	TENSION	L-L-H (MM)	RÉFÉRENCE ARTICLE
phase-cut dim 3 luminaires 220-240VAC	Noir		600-34-52	914133B0
phase-cut dim 3 luminaires 220-240VAC	Blanc		600-34-52	914133W0
phase-cut dim 6 luminaires 220-240VAC	Noir		1200-34-52	914134B0
phase-cut dim 6 luminaires 220-240VAC	Blanc		1200-34-52	914134W0
phase-cut dim 9 luminaires 220-240VAC	Noir		1800-34-52	914135B0
phase-cut dim 9 luminaires 220-240VAC	Blanc		1800-34-52	914135W0
phase cut TE 3 luminaires 110-277VAC	Noir		600-34-52	L914133B0
phase cut TE 3 luminaires 110-277VAC	Blanc		600-34-52	L914133W0
phase cut TE 6 luminaires 110-277VAC	Noir		1200-34-52	L914134B0
phase cut TE 6 luminaires 110-277VAC	Blanc		1200-34-52	L914134W0
phase cut TE 9 luminaires 110-277VAC	Noir		1800-34-52	L914135B0
phase cut TE 9 luminaires 110-277VAC	Blanc		1800-34-52	L914135W0


FL | MULTI CHANDELIER

MODÈLE	COLORIS	TENSION	Ø-H (MM)	RÉFÉRENCE ARTICLE
3 luminaires narrow slots 220-240VAC	Noir		380-44	914121BB0
3 luminaires narrow slots 220-240VAC	Noir + Aluminium brossé		380-44	914121BLO
3 luminaires narrow slots 220-240VAC	Noir + Champagne		380-44	914121BMO
3 luminaires narrow slots 220-240VAC	Noir + Bronze		380-44	914121BQ0
3 luminaires narrow slots 220-240VAC	Blanc		380-44	914121WW0
6 luminaires narrow slots 220-240VAC	Noir		380-44	914122BB0
6 luminaires narrow slots 220-240VAC	Noir + Aluminium brossé		380-44	914122BLO
6 luminaires narrow slots 220-240VAC	Noir + Champagne		380-44	914122BMO
6 luminaires narrow slots 220-240VAC	Noir + Bronze		380-44	914122BQ0
6 luminaires narrow slots 220-240VAC	Blanc		380-44	914122WW0
9 luminaires narrow slots 220-240VAC	Noir		380-44	914123BB0
9 luminaires narrow slots 220-240VAC	Noir + Aluminium brossé		380-44	914123BLO
9 luminaires narrow slots 220-240VAC	Noir + Champagne		380-44	914123BMO
9 luminaires narrow slots 220-240VAC	Noir + Bronze		380-44	914123BQ0
9 luminaires narrow slots 220-240VAC	Blanc		380-44	914123WW0
3 luminaires 110-277VAC	Noir		380-44	L914121BB0
3 luminaires 110-277VAC	Noir + Aluminium brossé		380-44	L914121BLO
3 luminaires 110-277VAC	Noir + Champagne		380-44	L914121BMO
3 luminaires 110-277VAC	Noir + Bronze		380-44	L914121BQ0
3 luminaires 110-277VAC	Blanc		380-44	L914121WW0
6 luminaires 110-277VAC	Noir		380-44	L914122BB0
6 luminaires 110-277VAC	Noir + Aluminium brossé		380-44	L914122BLO
6 luminaires 110-277VAC	Noir + Champagne		380-44	L914122BMO
6 luminaires 110-277VAC	Noir + Bronze		380-44	L914122BQ0
6 luminaires 110-277VAC	Blanc		380-44	L914122WW0
9 luminaires 110-277VAC	Noir		380-44	L914123BB0
9 luminaires 110-277VAC	Noir + Aluminium brossé		380-44	L914123BLO
9 luminaires 110-277VAC	Noir + Champagne		380-44	L914123BMO
9 luminaires 110-277VAC	Noir + Bronze		380-44	L914123BQ0
9 luminaires 110-277VAC	Blanc		380-44	L914123WW0

CROCHET LONG

MODÈLE	COLORIS	TENSION	Ø-H (MM)	RÉFÉRENCE ARTICLE
pour câble d'un diamètre de 4,25 à 5,5 mm	Blanc		15-49	90052083
pour câble d'un diamètre de 4,25 à 5,5 mm	Noir		15-49	90052084


MULTI CHANDELIER LV

MODÈLE	COLORIS	TENSION	Ø·H (MM)	RÉFÉRENCE ARTICLE
3 luminaires no slots 220-240VAC always use with hooks	Noir		380-44	914161BB0
3 luminaires no slots 220-240VAC always use with hooks	Noir + Aluminium		380-44	914161BL0
3 luminaires no slots 220-240VAC always use with hooks	Noir + Champagne		380-44	914161BM0
3 luminaires no slots 220-240VAC always use with hooks	Noir + Bronze		380-44	914161BQ0
3 luminaires no slots 220-240VAC always use with hooks	Blanc		380-44	914161WW0
6 luminaires no slots 220-240VAC always use with hooks	Noir		380-44	914162BB0
6 luminaires no slots 220-240VAC always use with hooks	Noir + Aluminium		380-44	914162BL0
6 luminaires no slots 220-240VAC always use with hooks	Noir + Champagne		380-44	914162BM0
6 luminaires no slots 220-240VAC always use with hooks	Noir + Bronze		380-44	914162BQ0
6 luminaires no slots 220-240VAC always use with hooks	Blanc		380-44	914162WW0
9 luminaires no slots 220-240VAC always use with hooks	Noir		380-44	914163BB0
9 luminaires no slots 220-240VAC always use with hooks	Noir + Aluminium		380-44	914163BL0
9 luminaires no slots 220-240VAC always use with hooks	Noir + Champagne		380-44	914163BM0
9 luminaires no slots 220-240VAC always use with hooks	Noir + Bronze		380-44	914163BQ0
9 luminaires no slots 220-240VAC always use with hooks	Blanc		380-44	914163WW0
3 luminaires no slots 110-277VAC always use with hooks	Noir		380-44	L914161BB0
3 luminaires no slots 110-277VAC always use with hooks	Noir + Aluminium		380-44	L914161BL0
3 luminaires no slots 110-277VAC always use with hooks	Noir + Champagne		380-44	L914161BM0
3 luminaires no slots 110-277VAC always use with hooks	Noir + Bronze		380-44	L914161BQ0
3 luminaires no slots 110-277VAC always use with hooks	Blanc		380-44	L914161WW0
6 luminaires no slots 110-277VAC always use with hooks	Noir		380-44	L914162BB0
6 luminaires no slots 110-277VAC always use with hooks	Noir + Aluminium		380-44	L914162BL0
6 luminaires no slots 110-277VAC always use with hooks	Noir + Champagne		380-44	L914162BM0
6 luminaires no slots 110-277VAC always use with hooks	Noir + Bronze		380-44	L914162BQ0
6 luminaires no slots 110-277VAC always use with hooks	Blanc		380-44	L914162WW0
9 luminaires no slots 110-277VAC always use with hooks	Noir		380-44	L914163BB0
9 luminaires no slots 110-277VAC always use with hooks	Noir + Aluminium		380-44	L914163BL0
9 luminaires no slots 110-277VAC always use with hooks	Noir + Champagne		380-44	L914163BM0
9 luminaires no slots 110-277VAC always use with hooks	Noir + Bronze		380-44	L914163BQ0
9 luminaires no slots 110-277VAC always use with hooks	Blanc		380-44	L914163WW0

ACCESSOIRES DE RAIL

**ADAPTATEUR DE RAIL**

MODÈLE	COLORIS	TENSION	L-H (MM)	RÉFÉRENCE ARTICLE
3-phase track 220-240VAC	Noir		158-46	914173B0
3-phase track 220-240VAC	Blanc		158-46	914173W0