



PROJET

MODÈLE

NOTES

QUANTITÉ

DATE



Luminaire suspendu en aluminium ; surface en Noir mat + Doré peinture humide ; structure de surface mate ; No matching RAL ; avec suspension de câble réglable max. 4000 mm en noir de sécurité ; culot GU10 ; type de lampe PAR16 ; max. 12W ; 18 V ; indice de protection IP20 ; Classe 3 ; cache-piton non inclus ;

## LUMINAIRE

Plafond  
Suspendu  
Noir mat + Doré  
Aucune correspondance RAL  
IP20  
Intérieur  
450 lm

## LED MODULE

3000 K  
CRI  $\geq 90$   
L70 / 55000h  
 $\leq 2$  SDCM (initial MacAdam)

## OPTIQUE


angle de faisceau 32°

## ÉLECTRIQUE

sans driver  
18 V  
système 7.0 W  
Classe 3

## PHYSIQUE

diamètre 115 mm  
hauteur 235 mm  
0.35 kg  
longueur du câble max. 2500 mm





## ACCESSOIRES DE MONTAGE

### AL | SINGLE BASE ROUND

| MODÈLE                                    | COLORIS   | TENSION | Ø-H (MM) | RÉFÉRENCE ARTICLE |
|-------------------------------------------|-----------|---------|----------|-------------------|
| phase-cut dim   incl. driver   220-240VAC | Noir      |         | 83-39    | 914112B0          |
| phase-cut dim   incl. driver   220-240VAC | Doré      |         | 83-39    | 914112G0          |
| phase-cut dim   incl. driver   220-240VAC | aluminium |         | 83-39    | 914112L0          |
| phase-cut dim   incl. driver   220-240VAC | Champagne |         | 83-39    | 914112M0          |
| phase-cut dim   incl. driver   220-240VAC | Bronze    |         | 83-39    | 914112Q0          |
| phase-cut dim   incl. driver   220-240VAC | Blanc     |         | 83-39    | 914112W0          |
| phase cut TE   incl. driver   110-277VAC  | Noir      |         | 83-39    | L914112B0         |
| phase cut TE   incl. driver   110-277VAC  | Doré      |         | 83-39    | L914112G0         |
| phase cut TE   incl. driver   110-277VAC  | aluminium |         | 83-39    | L914112L0         |
| phase cut TE   incl. driver   110-277VAC  | Champagne |         | 83-39    | L914112M0         |
| phase cut TE   incl. driver   110-277VAC  | Bronze    |         | 83-39    | L914112Q0         |
| phase cut TE   incl. driver   110-277VAC  | Blanc     |         | 83-39    | L914112W0         |

### BL | SEMI RECESSED SINGLE BASE ROUND

| MODÈLE                                   | COLORIS   | TENSION | Ø-H (MM) | RÉFÉRENCE ARTICLE |
|------------------------------------------|-----------|---------|----------|-------------------|
| incl. driver   220-240VAC                | Noir      |         | 84-72    | 914152B0          |
| incl. driver   220-240VAC                | aluminium |         | 83-72    | 914152L0          |
| incl. driver   220-240VAC                | Champagne |         | 83-72    | 914152M0          |
| incl. driver   220-240VAC                | Bronze    |         | 83-72    | 914152Q0          |
| incl. driver   220-240VAC                | Blanc     |         | 84-72    | 914152W0          |
| phase cut TE   incl. driver   110-277VAC | Noir      |         | 83-72    | L914152B0         |
| phase cut TE   incl. driver   110-277VAC | aluminium |         | 83-72    | L914152L0         |
| phase cut TE   incl. driver   110-277VAC | Champagne |         | 83-72    | L914152M0         |
| phase cut TE   incl. driver   110-277VAC | Bronze    |         | 83-72    | L914152Q0         |
| phase cut TE   incl. driver   110-277VAC | Blanc     |         | 83-72    | L914152W0         |

### EL | MULTI BASE LINEAR

| MODÈLE                                    | COLORIS | TENSION | L-L-H (MM) | RÉFÉRENCE ARTICLE |
|-------------------------------------------|---------|---------|------------|-------------------|
| phase-cut dim   3 luminaires   220-240VAC | Noir    |         | 600-34-52  | 914133B0          |
| phase-cut dim   3 luminaires   220-240VAC | Blanc   |         | 600-34-52  | 914133W0          |
| phase-cut dim   6 luminaires   220-240VAC | Noir    |         | 1200-34-52 | 914134B0          |
| phase-cut dim   6 luminaires   220-240VAC | Blanc   |         | 1200-34-52 | 914134W0          |
| phase-cut dim   9 luminaires   220-240VAC | Noir    |         | 1800-34-52 | 914135B0          |
| phase-cut dim   9 luminaires   220-240VAC | Blanc   |         | 1800-34-52 | 914135W0          |
| phase cut TE   3 luminaires   110-277VAC  | Noir    |         | 600-34-52  | L914133B0         |
| phase cut TE   3 luminaires   110-277VAC  | Blanc   |         | 600-34-52  | L914133W0         |
| phase cut TE   6 luminaires   110-277VAC  | Noir    |         | 1200-34-52 | L914134B0         |
| phase cut TE   6 luminaires   110-277VAC  | Blanc   |         | 1200-34-52 | L914134W0         |
| phase cut TE   9 luminaires   110-277VAC  | Noir    |         | 1800-34-52 | L914135B0         |
| phase cut TE   9 luminaires   110-277VAC  | Blanc   |         | 1800-34-52 | L914135W0         |


**FL | MULTI CHANDELIER**

| MODÈLE                                   | COLORIS                    | TENSION | Ø-H (MM) | RÉFÉRENCE ARTICLE |
|------------------------------------------|----------------------------|---------|----------|-------------------|
| 3 luminaires   narrow slots   220-240VAC | Noir                       |         | 380-44   | 914121BB0         |
| 3 luminaires   narrow slots   220-240VAC | Noir + Aluminium<br>brossé |         | 380-44   | 914121BLO         |
| 3 luminaires   narrow slots   220-240VAC | Noir + Champagne           |         | 380-44   | 914121BMO         |
| 3 luminaires   narrow slots   220-240VAC | Noir + Bronze              |         | 380-44   | 914121BQ0         |
| 3 luminaires   narrow slots   220-240VAC | Blanc                      |         | 380-44   | 914121WW0         |
| 6 luminaires   narrow slots   220-240VAC | Noir                       |         | 380-44   | 914122BB0         |
| 6 luminaires   narrow slots   220-240VAC | Noir + Aluminium<br>brossé |         | 380-44   | 914122BLO         |
| 6 luminaires   narrow slots   220-240VAC | Noir + Champagne           |         | 380-44   | 914122BMO         |
| 6 luminaires   narrow slots   220-240VAC | Noir + Bronze              |         | 380-44   | 914122BQ0         |
| 6 luminaires   narrow slots   220-240VAC | Blanc                      |         | 380-44   | 914122WW0         |
| 9 luminaires   narrow slots   220-240VAC | Noir                       |         | 380-44   | 914123BB0         |
| 9 luminaires   narrow slots   220-240VAC | Noir + Aluminium<br>brossé |         | 380-44   | 914123BLO         |
| 9 luminaires   narrow slots   220-240VAC | Noir + Champagne           |         | 380-44   | 914123BMO         |
| 9 luminaires   narrow slots   220-240VAC | Noir + Bronze              |         | 380-44   | 914123BQ0         |
| 9 luminaires   narrow slots   220-240VAC | Blanc                      |         | 380-44   | 914123WW0         |
| 3 luminaires   110-277VAC                | Noir                       |         | 380-44   | L914121BB0        |
| 3 luminaires   110-277VAC                | Noir + Aluminium<br>brossé |         | 380-44   | L914121BLO        |
| 3 luminaires   110-277VAC                | Noir + Champagne           |         | 380-44   | L914121BMO        |
| 3 luminaires   110-277VAC                | Noir + Bronze              |         | 380-44   | L914121BQ0        |
| 3 luminaires   110-277VAC                | Blanc                      |         | 380-44   | L914121WW0        |
| 6 luminaires   110-277VAC                | Noir                       |         | 380-44   | L914122BB0        |
| 6 luminaires   110-277VAC                | Noir + Aluminium<br>brossé |         | 380-44   | L914122BLO        |
| 6 luminaires   110-277VAC                | Noir + Champagne           |         | 380-44   | L914122BMO        |
| 6 luminaires   110-277VAC                | Noir + Bronze              |         | 380-44   | L914122BQ0        |
| 6 luminaires   110-277VAC                | Blanc                      |         | 380-44   | L914122WW0        |
| 9 luminaires   110-277VAC                | Noir                       |         | 380-44   | L914123BB0        |
| 9 luminaires   110-277VAC                | Noir + Aluminium<br>brossé |         | 380-44   | L914123BLO        |
| 9 luminaires   110-277VAC                | Noir + Champagne           |         | 380-44   | L914123BMO        |
| 9 luminaires   110-277VAC                | Noir + Bronze              |         | 380-44   | L914123BQ0        |
| 9 luminaires   110-277VAC                | Blanc                      |         | 380-44   | L914123WW0        |

**CROCHET LONG**

| MODÈLE                                    | COLORIS | TENSION | Ø-H (MM) | RÉFÉRENCE ARTICLE |
|-------------------------------------------|---------|---------|----------|-------------------|
| pour câble d'un diamètre de 4,25 à 5,5 mm | Blanc   |         | 15-49    | 90052083          |
| pour câble d'un diamètre de 4,25 à 5,5 mm | Noir    |         | 15-49    | 90052084          |


**MULTI CHANDELIER LV**

| MODÈLE                                                       | COLORIS          | TENSION | Ø·H (MM) | RÉFÉRENCE ARTICLE |
|--------------------------------------------------------------|------------------|---------|----------|-------------------|
| 3 luminaires   no slots   220-240VAC   always use with hooks | Noir             |         | 380-44   | 914161BB0         |
| 3 luminaires   no slots   220-240VAC   always use with hooks | Noir + Aluminium |         | 380-44   | 914161BL0         |
| 3 luminaires   no slots   220-240VAC   always use with hooks | Noir + Champagne |         | 380-44   | 914161BM0         |
| 3 luminaires   no slots   220-240VAC   always use with hooks | Noir + Bronze    |         | 380-44   | 914161BQ0         |
| 3 luminaires   no slots   220-240VAC   always use with hooks | Blanc            |         | 380-44   | 914161WW0         |
| 6 luminaires   no slots   220-240VAC   always use with hooks | Noir             |         | 380-44   | 914162BB0         |
| 6 luminaires   no slots   220-240VAC   always use with hooks | Noir + Aluminium |         | 380-44   | 914162BL0         |
| 6 luminaires   no slots   220-240VAC   always use with hooks | Noir + Champagne |         | 380-44   | 914162BM0         |
| 6 luminaires   no slots   220-240VAC   always use with hooks | Noir + Bronze    |         | 380-44   | 914162BQ0         |
| 6 luminaires   no slots   220-240VAC   always use with hooks | Blanc            |         | 380-44   | 914162WW0         |
| 9 luminaires   no slots   220-240VAC   always use with hooks | Noir             |         | 380-44   | 914163BB0         |
| 9 luminaires   no slots   220-240VAC   always use with hooks | Noir + Aluminium |         | 380-44   | 914163BL0         |
| 9 luminaires   no slots   220-240VAC   always use with hooks | Noir + Champagne |         | 380-44   | 914163BM0         |
| 9 luminaires   no slots   220-240VAC   always use with hooks | Noir + Bronze    |         | 380-44   | 914163BQ0         |
| 9 luminaires   no slots   220-240VAC   always use with hooks | Blanc            |         | 380-44   | 914163WW0         |
| 3 luminaires   no slots   110-277VAC   always use with hooks | Noir             |         | 380-44   | L914161BB0        |
| 3 luminaires   no slots   110-277VAC   always use with hooks | Noir + Aluminium |         | 380-44   | L914161BL0        |
| 3 luminaires   no slots   110-277VAC   always use with hooks | Noir + Champagne |         | 380-44   | L914161BM0        |
| 3 luminaires   no slots   110-277VAC   always use with hooks | Noir + Bronze    |         | 380-44   | L914161BQ0        |
| 3 luminaires   no slots   110-277VAC   always use with hooks | Blanc            |         | 380-44   | L914161WW0        |
| 6 luminaires   no slots   110-277VAC   always use with hooks | Noir             |         | 380-44   | L914162BB0        |
| 6 luminaires   no slots   110-277VAC   always use with hooks | Noir + Aluminium |         | 380-44   | L914162BL0        |
| 6 luminaires   no slots   110-277VAC   always use with hooks | Noir + Champagne |         | 380-44   | L914162BM0        |
| 6 luminaires   no slots   110-277VAC   always use with hooks | Noir + Bronze    |         | 380-44   | L914162BQ0        |
| 6 luminaires   no slots   110-277VAC   always use with hooks | Blanc            |         | 380-44   | L914162WW0        |
| 9 luminaires   no slots   110-277VAC   always use with hooks | Noir             |         | 380-44   | L914163BB0        |
| 9 luminaires   no slots   110-277VAC   always use with hooks | Noir + Aluminium |         | 380-44   | L914163BL0        |
| 9 luminaires   no slots   110-277VAC   always use with hooks | Noir + Champagne |         | 380-44   | L914163BM0        |
| 9 luminaires   no slots   110-277VAC   always use with hooks | Noir + Bronze    |         | 380-44   | L914163BQ0        |
| 9 luminaires   no slots   110-277VAC   always use with hooks | Blanc            |         | 380-44   | L914163WW0        |

**ACCESSOIRES DE RAIL**

**ADAPTATEUR DE RAIL**

| <b>MODÈLE</b>              | <b>COLORIS</b> | <b>TENSION</b> | <b>L-H (MM)</b> | <b>RÉFÉRENCE<br/>ARTICLE</b> |
|----------------------------|----------------|----------------|-----------------|------------------------------|
| 3-phase track   220-240VAC | Noir           |                | 158-46          | 914173B0                     |
| 3-phase track   220-240VAC | Blanc          |                | 158-46          | 914173W0                     |