



PROJET

MODÈLE

NOTES

QUANTITÉ

DATE



GÉNÉRAL

Plafond
Suspendu
Feutre calcaire
Aucune correspondance RAL
Intérieur


OPTIQUE

Opal

PHYSIQUE

diamètre 220 mm
hauteur 580 mm
0.45 kg

Élément acoustique en feutre de PET haute qualité doté de propriétés d'absorption du son ; 100% recyclable ; pour montage suspendu ; surface en Feutre calcaire ; No matching RAL ; avec suspension de câble réglable max. 2500 mm ;




ACCESSOIRES DE MONTAGE
AL | SINGLE BASE ROUND

MODÈLE	COLORIS	TENSION	Ø-H (MM)	RÉFÉRENCE ARTICLE
phase-cut dim incl. driver 220-240VAC	Noir		83-39	914112B0
phase-cut dim incl. driver 220-240VAC	Doré		83-39	914112G0
phase-cut dim incl. driver 220-240VAC	aluminium		83-39	914112L0
phase-cut dim incl. driver 220-240VAC	Champagne		83-39	914112M0
phase-cut dim incl. driver 220-240VAC	Bronze		83-39	914112Q0
phase-cut dim incl. driver 220-240VAC	Blanc		83-39	914112W0
phase cut TE incl. driver 110-277VAC	Noir		83-39	L914112B0
phase cut TE incl. driver 110-277VAC	Doré		83-39	L914112G0
phase cut TE incl. driver 110-277VAC	aluminium		83-39	L914112L0
phase cut TE incl. driver 110-277VAC	Champagne		83-39	L914112M0
phase cut TE incl. driver 110-277VAC	Bronze		83-39	L914112Q0
phase cut TE incl. driver 110-277VAC	Blanc		83-39	L914112W0

BL | SEMI RECESSED SINGLE BASE ROUND

MODÈLE	COLORIS	TENSION	Ø-H (MM)	RÉFÉRENCE ARTICLE
incl. driver 220-240VAC	Noir		84-72	914152B0
incl. driver 220-240VAC	aluminium		83-72	914152L0
incl. driver 220-240VAC	Champagne		83-72	914152M0
incl. driver 220-240VAC	Bronze		83-72	914152Q0
incl. driver 220-240VAC	Blanc		84-72	914152W0
phase cut TE incl. driver 110-277VAC	Noir		83-72	L914152B0
phase cut TE incl. driver 110-277VAC	aluminium		83-72	L914152L0
phase cut TE incl. driver 110-277VAC	Champagne		83-72	L914152M0
phase cut TE incl. driver 110-277VAC	Bronze		83-72	L914152Q0
phase cut TE incl. driver 110-277VAC	Blanc		83-72	L914152W0

EL | MULTI BASE LINEAR

MODÈLE	COLORIS	TENSION	L-L-H (MM)	RÉFÉRENCE ARTICLE
phase-cut dim 3 luminaires 220-240VAC	Noir		600-34-52	914133B0
phase-cut dim 3 luminaires 220-240VAC	Blanc		600-34-52	914133W0
phase-cut dim 6 luminaires 220-240VAC	Noir		1200-34-52	914134B0
phase-cut dim 6 luminaires 220-240VAC	Blanc		1200-34-52	914134W0
phase-cut dim 9 luminaires 220-240VAC	Noir		1800-34-52	914135B0
phase-cut dim 9 luminaires 220-240VAC	Blanc		1800-34-52	914135W0
phase cut TE 3 luminaires 110-277VAC	Noir		600-34-52	L914133B0
phase cut TE 3 luminaires 110-277VAC	Blanc		600-34-52	L914133W0
phase cut TE 6 luminaires 110-277VAC	Noir		1200-34-52	L914134B0
phase cut TE 6 luminaires 110-277VAC	Blanc		1200-34-52	L914134W0
phase cut TE 9 luminaires 110-277VAC	Noir		1800-34-52	L914135B0
phase cut TE 9 luminaires 110-277VAC	Blanc		1800-34-52	L914135W0


FL | MULTI CHANDELIER

MODÈLE	COLORIS	TENSION	Ø·H (MM)	RÉFÉRENCE ARTICLE
3 luminaires wide slots 220-240VAC	Noir		380-44	914124BB0
3 luminaires wide slots 220-240VAC	Noir + Aluminium brossé		380-44	914124BLO
3 luminaires wide slots 220-240VAC	Noir + Champagne		380-44	914124BMO
3 luminaires wide slots 220-240VAC	Noir + Bronze		380-44	914124BQ0
3 luminaires wide slots 220-240VAC	Blanc		380-44	914124WW0
6 luminaires wide slots 220-240VAC	Noir		380-44	914125BB0
6 luminaires wide slots 220-240VAC	Noir + Aluminium brossé		380-44	914125BLO
6 luminaires wide slots 220-240VAC	Noir + Champagne		380-44	914125BMO
6 luminaires wide slots 220-240VAC	Noir + Bronze		380-44	914125BQ0
6 luminaires wide slots 220-240VAC	Blanc		380-44	914125WW0
9 luminaires wide slots 220-240VAC	Noir		380-44	914126BB0
9 luminaires wide slots 220-240VAC	Noir + Aluminium brossé		380-44	914126BLO
9 luminaires wide slots 220-240VAC	Noir + Champagne		380-44	914126BMO
9 luminaires wide slots 220-240VAC	Noir + Bronze		380-44	914126BQ0
9 luminaires wide slots 220-240VAC	Blanc		380-44	914126WW0
3 luminaires 110-277VAC	Noir		380-44	L914124BB0
3 luminaires 110-277VAC	Noir + Aluminium brossé		380-44	L914124BLO
3 luminaires 110-277VAC	Noir + Champagne		380-44	L914124BMO
3 luminaires 110-277VAC	Noir + Bronze		380-44	L914124BQ0
3 luminaires 110-277VAC	Blanc		380-44	L914124WW0
6 luminaires 110-277VAC	Noir		380-44	L914125BB0
6 luminaires 110-277VAC	Noir + Aluminium brossé		380-44	L914125BLO
6 luminaires 110-277VAC	Noir + Champagne		380-44	L914125BMO
6 luminaires 110-277VAC	Noir + Bronze		380-44	L914125BQ0
6 luminaires 110-277VAC	Blanc		380-44	L914125WW0
9 luminaires 110-277VAC	Noir		380-44	L914126BB0
9 luminaires 110-277VAC	Noir + Aluminium brossé		380-44	L914126BLO
9 luminaires 110-277VAC	Noir + Champagne		380-44	L914126BMO
9 luminaires 110-277VAC	Noir + Bronze		380-44	L914126BQ0
9 luminaires 110-277VAC	Blanc		380-44	L914126WW0

CROCHET LONG

MODÈLE	COLORIS	TENSION	Ø·H (MM)	RÉFÉRENCE ARTICLE
pour câble d'un diamètre de 4,25 à 5,5 mm	Blanc		15-49	90052083
pour câble d'un diamètre de 4,25 à 5,5 mm	Noir		15-49	90052084


MULTI CHANDELIER LV

MODÈLE	COLORIS	TENSION	Ø·H (MM)	RÉFÉRENCE ARTICLE
3 luminaires no slots 220-240VAC always use with hooks	Noir		380-44	914161BB0
3 luminaires no slots 220-240VAC always use with hooks	Noir + Aluminium		380-44	914161BL0
3 luminaires no slots 220-240VAC always use with hooks	Noir + Champagne		380-44	914161BM0
3 luminaires no slots 220-240VAC always use with hooks	Noir + Bronze		380-44	914161BQ0
3 luminaires no slots 220-240VAC always use with hooks	Blanc		380-44	914161WW0
6 luminaires no slots 220-240VAC always use with hooks	Noir		380-44	914162BB0
6 luminaires no slots 220-240VAC always use with hooks	Noir + Aluminium		380-44	914162BL0
6 luminaires no slots 220-240VAC always use with hooks	Noir + Champagne		380-44	914162BM0
6 luminaires no slots 220-240VAC always use with hooks	Noir + Bronze		380-44	914162BQ0
6 luminaires no slots 220-240VAC always use with hooks	Blanc		380-44	914162WW0
9 luminaires no slots 220-240VAC always use with hooks	Noir		380-44	914163BB0
9 luminaires no slots 220-240VAC always use with hooks	Noir + Aluminium		380-44	914163BL0
9 luminaires no slots 220-240VAC always use with hooks	Noir + Champagne		380-44	914163BM0
9 luminaires no slots 220-240VAC always use with hooks	Noir + Bronze		380-44	914163BQ0
9 luminaires no slots 220-240VAC always use with hooks	Blanc		380-44	914163WW0
3 luminaires no slots 110-277VAC always use with hooks	Noir		380-44	L914161BB0
3 luminaires no slots 110-277VAC always use with hooks	Noir + Aluminium		380-44	L914161BL0
3 luminaires no slots 110-277VAC always use with hooks	Noir + Champagne		380-44	L914161BM0
3 luminaires no slots 110-277VAC always use with hooks	Noir + Bronze		380-44	L914161BQ0
3 luminaires no slots 110-277VAC always use with hooks	Blanc		380-44	L914161WW0
6 luminaires no slots 110-277VAC always use with hooks	Noir		380-44	L914162BB0
6 luminaires no slots 110-277VAC always use with hooks	Noir + Aluminium		380-44	L914162BL0
6 luminaires no slots 110-277VAC always use with hooks	Noir + Champagne		380-44	L914162BM0
6 luminaires no slots 110-277VAC always use with hooks	Noir + Bronze		380-44	L914162BQ0
6 luminaires no slots 110-277VAC always use with hooks	Blanc		380-44	L914162WW0
9 luminaires no slots 110-277VAC always use with hooks	Noir		380-44	L914163BB0
9 luminaires no slots 110-277VAC always use with hooks	Noir + Aluminium		380-44	L914163BL0
9 luminaires no slots 110-277VAC always use with hooks	Noir + Champagne		380-44	L914163BM0
9 luminaires no slots 110-277VAC always use with hooks	Noir + Bronze		380-44	L914163BQ0
9 luminaires no slots 110-277VAC always use with hooks	Blanc		380-44	L914163WW0

238600LFO**BASE UNIQUE LV**

MODÈLE	COLORIS	TENSION	Ø-H (MM)	RÉFÉRENCE ARTICLE
DALI-2 incl. driver 220-240VAC	Noir		116-28	914117B0
DALI-2 incl. driver 220-240VAC	Blanc		116-28	914117W0

ACCESSOIRES DE RAIL**ADAPTATEUR DE RAIL**

MODÈLE	COLORIS	TENSION	L-H (MM)	RÉFÉRENCE ARTICLE
3-phase track 220-240VAC	Noir		158-46	914173B0
3-phase track 220-240VAC	Blanc		158-46	914173W0