



PROJECT

TYPE

OPMERKINGEN

HOEVEELHEID

DATUM



Buisvormige pendelarmatuur voor plafondmontage van gegoten aluminium; oppervlak Matwit; gepoedercoat, mat textuur; No matching RAL; inclusief regelbare kabelophanging max. 2500mm in Zuiverwit; met COB (Chip on Board) technologie voor maximale efficiëntie; lichtkleur 3000 K; ≤ 2 SDCM (initial MacAdam); CRI ≥ 90 ; 18 V; stralingshoek 54°; beschermingsgraad IP20; Klasse 3; driver inbegrepen; lichtbron kan worden vervangen door Wever & Ducré of door een vakman met uitdrukkelijke toestemming; driver vervangbaar door gekwalificeerd personeel;

ARMATUUR

Plafond
Pendel
Mat wit
Geen overeenkomende RAL
IP20
Interieur
520 lm

LED MODULE

3000 K
CRI ≥ 90
L80 / 50000h
 ≤ 2 SDCM (initial MacAdam)
 ≤ 2 SDCM (initial MacAdam)

OPTISCH


Wide (standard)
stralingshoek 54°

ELEKTRISCH

18 V
systeem 6.0 W
Klasse 3

FYSIEK

diameter 26 mm
hoogte 300 mm
0.12 kg
Lengte kabel max. 2500 mm
kies je basis





Onderhoudsfactor

Bedrijfstijd [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.99	0.98	0.97	0.96	0.95
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Onderhoudsfactor ruimte
MF	Onderhoudsfactor	LLMF	Lumenbehoudfactor lichtbron
LMF ^a	Behoudfactor armatuur	LSF	Overlevingsfactor lichtbron

^aVolgens "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. De waarden moeten bepaald worden door de planningverantwoordelijke.

MONTAGEACCESSOIRES

AL | SINGLE BASE ROUND

TYPE	KLEUR	SPANNING	Ø-H (MM)	ARTIKEL NUMMER
phase-cut dim incl. driver 220-240VAC	Zwart		83-39	914112B0
phase-cut dim incl. driver 220-240VAC	Goud		83-39	914112G0
phase-cut dim incl. driver 220-240VAC	Aluminium		83-39	914112L0
phase-cut dim incl. driver 220-240VAC	Champagne		83-39	914112M0
phase-cut dim incl. driver 220-240VAC	Brons		83-39	914112Q0
phase-cut dim incl. driver 220-240VAC	Wit		83-39	914112W0
phase cut TE incl. driver 110-277VAC	Zwart		83-39	L914112B0
phase cut TE incl. driver 110-277VAC	Goud		83-39	L914112G0
phase cut TE incl. driver 110-277VAC	Aluminium		83-39	L914112L0
phase cut TE incl. driver 110-277VAC	Champagne		83-39	L914112M0
phase cut TE incl. driver 110-277VAC	Brons		83-39	L914112Q0
phase cut TE incl. driver 110-277VAC	Wit		83-39	L914112W0

BL | SEMI RECESSED SINGLE BASE ROUND

TYPE	KLEUR	SPANNING	Ø-H (MM)	ARTIKEL NUMMER
incl. driver 220-240VAC	Zwart		84-72	914152B0
incl. driver 220-240VAC	Aluminium		83-72	914152L0
incl. driver 220-240VAC	Champagne		83-72	914152M0
incl. driver 220-240VAC	Brons		83-72	914152Q0
incl. driver 220-240VAC	Wit		84-72	914152W0
phase cut TE incl. driver 110-277VAC	Zwart		83-72	L914152B0
phase cut TE incl. driver 110-277VAC	Aluminium		83-72	L914152L0
phase cut TE incl. driver 110-277VAC	Champagne		83-72	L914152M0
phase cut TE incl. driver 110-277VAC	Brons		83-72	L914152Q0
phase cut TE incl. driver 110-277VAC	Wit		83-72	L914152W0

EL | MULTI BASE LINEAR

TYPE	KLEUR	SPANNING	L-B-H (MM)	ARTIKEL NUMMER
phase-cut dim 3 luminaires 220-240VAC	Zwart		600-34-52	914133B0
phase-cut dim 3 luminaires 220-240VAC	Wit		600-34-52	914133W0
phase-cut dim 6 luminaires 220-240VAC	Zwart		1200-34-52	914134B0
phase-cut dim 6 luminaires 220-240VAC	Wit		1200-34-52	914134W0
phase-cut dim 9 luminaires 220-240VAC	Zwart		1800-34-52	914135B0
phase-cut dim 9 luminaires 220-240VAC	Wit		1800-34-52	914135W0
phase cut TE 3 luminaires 110-277VAC	Zwart		600-34-52	L914133B0
phase cut TE 3 luminaires 110-277VAC	Wit		600-34-52	L914133W0
phase cut TE 6 luminaires 110-277VAC	Zwart		1200-34-52	L914134B0
phase cut TE 6 luminaires 110-277VAC	Wit		1200-34-52	L914134W0
phase cut TE 9 luminaires 110-277VAC	Zwart		1800-34-52	L914135B0
phase cut TE 9 luminaires 110-277VAC	Wit		1800-34-52	L914135W0

[279271W5] De technische gegevens vertegenwoordigen nominale waarden voor een omgevingstemperatuur van 25 °C. Voor de gegevenswaarden voor de lichtstroom geldt initieel een tolerantie van +/- 10%, voor het elektrische aansluitvermogen geldt in eerste instantie een tolerantie van +/- 10% en voor de kleurtemperatuur geldt in eerste instantie een tolerantie van +/- 150 K. Wij aanvaarden geen aansprakelijkheid voor druk- en zetfouten. The general terms and conditions of Wever & Ducré BV apply.

© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com


FL | MULTI CHANDELIER

TYPE	KLEUR	SPANNING	Ø-H (MM)	ARTIKEL NUMMER
3 luminaires narrow slots 220-240VAC	Zwart		380-44	914121BB0
3 luminaires narrow slots 220-240VAC	Matzward + Aluminium geborsteld		380-44	914121BLO
3 luminaires narrow slots 220-240VAC	Zwart + Champagne		380-44	914121BM0
3 luminaires narrow slots 220-240VAC	Zwart + brons		380-44	914121BQ0
3 luminaires narrow slots 220-240VAC	Wit		380-44	914121WW0
6 luminaires narrow slots 220-240VAC	Zwart		380-44	914122BB0
6 luminaires narrow slots 220-240VAC	Matzward + Aluminium geborsteld		380-44	914122BLO
6 luminaires narrow slots 220-240VAC	Zwart + Champagne		380-44	914122BM0
6 luminaires narrow slots 220-240VAC	Zwart + brons		380-44	914122BQ0
6 luminaires narrow slots 220-240VAC	Wit		380-44	914122WW0
9 luminaires narrow slots 220-240VAC	Zwart		380-44	914123BB0
9 luminaires narrow slots 220-240VAC	Matzward + Aluminium geborsteld		380-44	914123BLO
9 luminaires narrow slots 220-240VAC	Zwart + Champagne		380-44	914123BM0
9 luminaires narrow slots 220-240VAC	Zwart + brons		380-44	914123BQ0
9 luminaires narrow slots 220-240VAC	Wit		380-44	914123WW0
3 luminaires 110-277VAC	Zwart		380-44	L914121BB0
3 luminaires 110-277VAC	Matzward + Aluminium geborsteld		380-44	L914121BLO
3 luminaires 110-277VAC	Zwart + Champagne		380-44	L914121BM0
3 luminaires 110-277VAC	Zwart + brons		380-44	L914121BQ0
3 luminaires 110-277VAC	Wit		380-44	L914121WW0
6 luminaires 110-277VAC	Zwart		380-44	L914122BB0
6 luminaires 110-277VAC	Matzward + Aluminium geborsteld		380-44	L914122BLO
6 luminaires 110-277VAC	Zwart + Champagne		380-44	L914122BM0
6 luminaires 110-277VAC	Zwart + brons		380-44	L914122BQ0
6 luminaires 110-277VAC	Wit		380-44	L914122WW0
9 luminaires 110-277VAC	Zwart		380-44	L914123BB0
9 luminaires 110-277VAC	Matzward + Aluminium geborsteld		380-44	L914123BLO
9 luminaires 110-277VAC	Zwart + Champagne		380-44	L914123BM0
9 luminaires 110-277VAC	Zwart + brons		380-44	L914123BQ0
9 luminaires 110-277VAC	Wit		380-44	L914123WW0

HAAK LANG

TYPE	KLEUR	SPANNING	Ø-H (MM)	ARTIKEL NUMMER
voor kabel 4.25-5.5mm diameter	Wit		15-49	90052083
voor kabel 4.25-5.5mm diameter	Zwart		15-49	90052084


MULTI CHANDELIER LV

TYPE	KLEUR	SPANNING	Ø-H (MM)	ARTIKEL NUMMER
3 luminaires no slots 220-240VAC always use with hooks	Zwart		380-44	914161BB0
3 luminaires no slots 220-240VAC always use with hooks	Zwart + Aluminium		380-44	914161BLO
3 luminaires no slots 220-240VAC always use with hooks	Zwart + Champagne		380-44	914161BM0
3 luminaires no slots 220-240VAC always use with hooks	Zwart + brons		380-44	914161BQ0
3 luminaires no slots 220-240VAC always use with hooks	Wit		380-44	914161WW0
6 luminaires no slots 220-240VAC always use with hooks	Zwart		380-44	914162BB0
6 luminaires no slots 220-240VAC always use with hooks	Zwart + Aluminium		380-44	914162BLO
6 luminaires no slots 220-240VAC always use with hooks	Zwart + Champagne		380-44	914162BM0
6 luminaires no slots 220-240VAC always use with hooks	Zwart + brons		380-44	914162BQ0
6 luminaires no slots 220-240VAC always use with hooks	Wit		380-44	914162WW0
9 luminaires no slots 220-240VAC always use with hooks	Zwart		380-44	914163BB0
9 luminaires no slots 220-240VAC always use with hooks	Zwart + Aluminium		380-44	914163BLO
9 luminaires no slots 220-240VAC always use with hooks	Zwart + Champagne		380-44	914163BM0
9 luminaires no slots 220-240VAC always use with hooks	Zwart + brons		380-44	914163BQ0
9 luminaires no slots 220-240VAC always use with hooks	Wit		380-44	914163WW0
3 luminaires no slots 110-277VAC always use with hooks	Zwart		380-44	L914161BB0
3 luminaires no slots 110-277VAC always use with hooks	Zwart + Aluminium		380-44	L914161BLO
3 luminaires no slots 110-277VAC always use with hooks	Zwart + Champagne		380-44	L914161BM0
3 luminaires no slots 110-277VAC always use with hooks	Zwart + brons		380-44	L914161BQ0
3 luminaires no slots 110-277VAC always use with hooks	Wit		380-44	L914161WW0
6 luminaires no slots 110-277VAC always use with hooks	Zwart		380-44	L914162BB0
6 luminaires no slots 110-277VAC always use with hooks	Zwart + Aluminium		380-44	L914162BLO
6 luminaires no slots 110-277VAC always use with hooks	Zwart + Champagne		380-44	L914162BM0
6 luminaires no slots 110-277VAC always use with hooks	Zwart + brons		380-44	L914162BQ0
6 luminaires no slots 110-277VAC always use with hooks	Wit		380-44	L914162WW0
9 luminaires no slots 110-277VAC always use with hooks	Zwart		380-44	L914163BB0
9 luminaires no slots 110-277VAC always use with hooks	Zwart + Aluminium		380-44	L914163BLO
9 luminaires no slots 110-277VAC always use with hooks	Zwart + Champagne		380-44	L914163BM0
9 luminaires no slots 110-277VAC always use with hooks	Zwart + brons		380-44	L914163BQ0
9 luminaires no slots 110-277VAC always use with hooks	Wit		380-44	L914163WW0

TRACK ACCESSOIRES

**TRACKADAPTER**

TYPE	KLEUR	SPANNING	L·H (MM)	ARTIKEL NUMMER
3-phase track 220-240VAC	Zwart		158·46	914173B0
3-phase track 220-240VAC	Wit		158·46	914173W0