



**PROJECT**

**TYPE**

**OPMERKINGEN**

**HOEVEELHEID**

**DATUM**



Cilindrische pendelarmatuur voor plafondmontage van gegoten aluminium; oppervlak Matzwart; gepoedercoat, mat textuur; No matching RAL; inclusief regelbare buisophanging max. 2500mm; met COB (Chip on Board) technologie voor maximale efficiëntie; lichtkleur 3000 K; CRI ≥ 90; 18 V; beschermingsgraad IP20; Klasse 3; driver inbegrepen;

**ARMATUUR**

Plafond  
Pendel  
Matzwart  
Geen overeenkomende RAL  
IP20  
Interieur  
520 lm

**LED MODULE**

3000 K  
CRI ≥ 90  
L80 / 50000h  
≤ 2 SDCM (initial MacAdam)

**OPTISCH**


Wide  
stralingshoek 54°

**ELEKTRISCH**

18 V  
systeem 6.0 W  
Klasse 3

**FYSIEK**

diameter 28 mm  
hoogte 300 mm  
0.12 kg  
Lengte kabel max. 2500 mm  
kies je basis





## MONTAGEACCESSOIRES

### AL | SINGLE BASE ROUND

| TYPE                                      | KLEUR     | SPANNING | Ø·H (MM) | ARTIKEL NUMMER |
|-------------------------------------------|-----------|----------|----------|----------------|
| phase-cut dim   incl. driver   220-240VAC | Zwart     |          | 83-39    | 914112B0       |
| phase-cut dim   incl. driver   220-240VAC | Goud      |          | 83-39    | 914112G0       |
| phase-cut dim   incl. driver   220-240VAC | Aluminium |          | 83-39    | 914112L0       |
| phase-cut dim   incl. driver   220-240VAC | Champagne |          | 83-39    | 914112M0       |
| phase-cut dim   incl. driver   220-240VAC | Brons     |          | 83-39    | 914112Q0       |
| phase-cut dim   incl. driver   220-240VAC | Wit       |          | 83-39    | 914112W0       |

### BL | SEMI RECESSED SINGLE BASE ROUND

| TYPE                      | KLEUR     | SPANNING | Ø·H (MM) | ARTIKEL NUMMER |
|---------------------------|-----------|----------|----------|----------------|
| incl. driver   220-240VAC | Zwart     |          | 84-72    | 914152B0       |
| incl. driver   220-240VAC | Aluminium |          | 83-72    | 914152L0       |
| incl. driver   220-240VAC | Champagne |          | 83-72    | 914152M0       |
| incl. driver   220-240VAC | Brons     |          | 83-72    | 914152Q0       |
| incl. driver   220-240VAC | Wit       |          | 84-72    | 914152W0       |

### EL | MULTI BASE LINEAR

| TYPE                                      | KLEUR | SPANNING | L·B·H (MM) | ARTIKEL NUMMER |
|-------------------------------------------|-------|----------|------------|----------------|
| phase-cut dim   3 luminaires   220-240VAC | Zwart |          | 600-34-52  | 914133B0       |
| phase-cut dim   3 luminaires   220-240VAC | Wit   |          | 600-34-52  | 914133W0       |
| phase-cut dim   6 luminaires   220-240VAC | Zwart |          | 1200-34-52 | 914134B0       |
| phase-cut dim   6 luminaires   220-240VAC | Wit   |          | 1200-34-52 | 914134W0       |
| phase-cut dim   9 luminaires   220-240VAC | Zwart |          | 1800-34-52 | 914135B0       |
| phase-cut dim   9 luminaires   220-240VAC | Wit   |          | 1800-34-52 | 914135W0       |

### FL | MULTI CHANDELIER

| TYPE                                     | KLEUR                           | SPANNING | Ø·H (MM) | ARTIKEL NUMMER |
|------------------------------------------|---------------------------------|----------|----------|----------------|
| 3 luminaires   narrow slots   220-240VAC | Zwart                           |          | 380-44   | 914121BB0      |
| 3 luminaires   narrow slots   220-240VAC | Matzwart + Aluminium geborsteld |          | 380-44   | 914121BL0      |
| 3 luminaires   narrow slots   220-240VAC | Zwart + Champagne               |          | 380-44   | 914121BM0      |
| 3 luminaires   narrow slots   220-240VAC | Zwart + brons                   |          | 380-44   | 914121BQ0      |
| 3 luminaires   narrow slots   220-240VAC | Wit                             |          | 380-44   | 914121WW0      |
| 6 luminaires   narrow slots   220-240VAC | Zwart                           |          | 380-44   | 914122BB0      |
| 6 luminaires   narrow slots   220-240VAC | Matzwart + Aluminium geborsteld |          | 380-44   | 914122BL0      |
| 6 luminaires   narrow slots   220-240VAC | Zwart + Champagne               |          | 380-44   | 914122BM0      |
| 6 luminaires   narrow slots   220-240VAC | Zwart + brons                   |          | 380-44   | 914122BQ0      |
| 6 luminaires   narrow slots   220-240VAC | Wit                             |          | 380-44   | 914122WW0      |
| 9 luminaires   narrow slots   220-240VAC | Zwart                           |          | 380-44   | 914123BB0      |
| 9 luminaires   narrow slots   220-240VAC | Matzwart + Aluminium geborsteld |          | 380-44   | 914123BL0      |
| 9 luminaires   narrow slots   220-240VAC | Zwart + Champagne               |          | 380-44   | 914123BM0      |
| 9 luminaires   narrow slots   220-240VAC | Zwart + brons                   |          | 380-44   | 914123BQ0      |
| 9 luminaires   narrow slots   220-240VAC | Wit                             |          | 380-44   | 914123WW0      |

### HAAK LANG

| TYPE                           | KLEUR | SPANNING | Ø·H (MM) | ARTIKEL NUMMER |
|--------------------------------|-------|----------|----------|----------------|
| voor kabel 4.25-5.5mm diameter | Wit   |          | 15-49    | 90052083       |
| voor kabel 4.25-5.5mm diameter | Zwart |          | 15-49    | 90052084       |


**MULTI CHANDELIER LV**

| TYPE                                                         | KLEUR             | SPANNING | Ø-H (MM) | ARTIKEL NUMMER |
|--------------------------------------------------------------|-------------------|----------|----------|----------------|
| 3 luminaires   no slots   220-240VAC   always use with hooks | Zwart             |          | 380-44   | 914161BB0      |
| 3 luminaires   no slots   220-240VAC   always use with hooks | Zwart + Aluminium |          | 380-44   | 914161BL0      |
| 3 luminaires   no slots   220-240VAC   always use with hooks | Zwart + Champagne |          | 380-44   | 914161BM0      |
| 3 luminaires   no slots   220-240VAC   always use with hooks | Zwart + brons     |          | 380-44   | 914161BQ0      |
| 3 luminaires   no slots   220-240VAC   always use with hooks | Wit               |          | 380-44   | 914161WW0      |
| 6 luminaires   no slots   220-240VAC   always use with hooks | Zwart             |          | 380-44   | 914162BB0      |
| 6 luminaires   no slots   220-240VAC   always use with hooks | Zwart + Aluminium |          | 380-44   | 914162BL0      |
| 6 luminaires   no slots   220-240VAC   always use with hooks | Zwart + Champagne |          | 380-44   | 914162BM0      |
| 6 luminaires   no slots   220-240VAC   always use with hooks | Zwart + brons     |          | 380-44   | 914162BQ0      |
| 6 luminaires   no slots   220-240VAC   always use with hooks | Wit               |          | 380-44   | 914162WW0      |
| 9 luminaires   no slots   220-240VAC   always use with hooks | Zwart             |          | 380-44   | 914163BB0      |
| 9 luminaires   no slots   220-240VAC   always use with hooks | Zwart + Aluminium |          | 380-44   | 914163BL0      |
| 9 luminaires   no slots   220-240VAC   always use with hooks | Zwart + Champagne |          | 380-44   | 914163BM0      |
| 9 luminaires   no slots   220-240VAC   always use with hooks | Zwart + brons     |          | 380-44   | 914163BQ0      |
| 9 luminaires   no slots   220-240VAC   always use with hooks | Wit               |          | 380-44   | 914163WW0      |

**TRACK ACCESSOIRES**
**TRACKADAPTER**

| TYPE                       | KLEUR | SPANNING | L-H (MM) | ARTIKEL NUMMER |
|----------------------------|-------|----------|----------|----------------|
| 3-phase track   220-240VAC | Zwart |          | 158-46   | 914173B0       |
| 3-phase track   220-240VAC | Wit   |          | 158-46   | 914173W0       |