



PROJECT

TYPE

OPMERKINGEN

HOEVEELHEID

DATUM



Cilindrische pendelarmatuur voor plafondmontage van gegoten aluminium; oppervlak Matzwart; gepoedercoat, mat textuur; No matching RAL; inclusief regelbare buisophanging max. 2500mm; met COB (Chip on Board) technologie voor maximale efficiëntie; lichtkleur 3000 K; CRI $\geq$ 90; 17 V; beschermingsgraad IP20; Klasse 3; driver inbegrepen;

ARMATUUR

Plafond
Pendel
Matzwart
Geen overeenkomende RAL
IP20
Interieur
590 lm

LED MODULE

3000 K
CRI $\geq$ 90
L80 / 50000h
 $\leq$ 2 SDCM (initial MacAdam)

OPTISCH


Wide
stralingshoek 75°

ELEKTRISCH

17 V
systeem 6.0 W
Klasse 3

FYSIEK

diameter 48 mm
hoogte 260 mm
0.12 kg
Lengte kabel max. 2500 mm
kies je basis





MONTAGEACCESSOIRES

AL | SINGLE BASE ROUND

TYPE	KLEUR	SPANNING	Ø·H (MM)	ARTIKEL NUMMER
phase-cut dim incl. driver 220-240VAC	Zwart		83-39	914112B0
phase-cut dim incl. driver 220-240VAC	Goud		83-39	914112G0
phase-cut dim incl. driver 220-240VAC	Aluminium		83-39	914112L0
phase-cut dim incl. driver 220-240VAC	Champagne		83-39	914112M0
phase-cut dim incl. driver 220-240VAC	Brons		83-39	914112Q0
phase-cut dim incl. driver 220-240VAC	Wit		83-39	914112W0

BL | SEMI RECESSED SINGLE BASE ROUND

TYPE	KLEUR	SPANNING	Ø·H (MM)	ARTIKEL NUMMER
incl. driver 220-240VAC	Zwart		84-72	914152B0
incl. driver 220-240VAC	Aluminium		83-72	914152L0
incl. driver 220-240VAC	Champagne		83-72	914152M0
incl. driver 220-240VAC	Brons		83-72	914152Q0
incl. driver 220-240VAC	Wit		84-72	914152W0

EL | MULTI BASE LINEAR

TYPE	KLEUR	SPANNING	L·B·H (MM)	ARTIKEL NUMMER
phase-cut dim 3 luminaires 220-240VAC	Zwart		600-34-52	914133B0
phase-cut dim 3 luminaires 220-240VAC	Wit		600-34-52	914133W0
phase-cut dim 6 luminaires 220-240VAC	Zwart		1200-34-52	914134B0
phase-cut dim 6 luminaires 220-240VAC	Wit		1200-34-52	914134W0
phase-cut dim 9 luminaires 220-240VAC	Zwart		1800-34-52	914135B0
phase-cut dim 9 luminaires 220-240VAC	Wit		1800-34-52	914135W0

FL | MULTI CHANDELIER

TYPE	KLEUR	SPANNING	Ø·H (MM)	ARTIKEL NUMMER
3 luminaires narrow slots 220-240VAC	Zwart		380-44	914121BB0
3 luminaires narrow slots 220-240VAC	Matzwart + Aluminium geborsteld		380-44	914121BL0
3 luminaires narrow slots 220-240VAC	Zwart + Champagne		380-44	914121BM0
3 luminaires narrow slots 220-240VAC	Zwart + brons		380-44	914121BQ0
3 luminaires narrow slots 220-240VAC	Wit		380-44	914121WW0
6 luminaires narrow slots 220-240VAC	Zwart		380-44	914122BB0
6 luminaires narrow slots 220-240VAC	Matzwart + Aluminium geborsteld		380-44	914122BL0
6 luminaires narrow slots 220-240VAC	Zwart + Champagne		380-44	914122BM0
6 luminaires narrow slots 220-240VAC	Zwart + brons		380-44	914122BQ0
6 luminaires narrow slots 220-240VAC	Wit		380-44	914122WW0
9 luminaires narrow slots 220-240VAC	Zwart		380-44	914123BB0
9 luminaires narrow slots 220-240VAC	Matzwart + Aluminium geborsteld		380-44	914123BL0
9 luminaires narrow slots 220-240VAC	Zwart + Champagne		380-44	914123BM0
9 luminaires narrow slots 220-240VAC	Zwart + brons		380-44	914123BQ0
9 luminaires narrow slots 220-240VAC	Wit		380-44	914123WW0

HAAK LANG

TYPE	KLEUR	SPANNING	Ø·H (MM)	ARTIKEL NUMMER
voor kabel 4.25-5.5mm diameter	Wit		15-49	90052083
voor kabel 4.25-5.5mm diameter	Zwart		15-49	90052084


MULTI CHANDELIER LV

TYPE	KLEUR	SPANNING	Ø-H (MM)	ARTIKEL NUMMER
3 luminaires no slots 220-240VAC always use with hooks	Zwart		380-44	914161BB0
3 luminaires no slots 220-240VAC always use with hooks	Zwart + Aluminium		380-44	914161BL0
3 luminaires no slots 220-240VAC always use with hooks	Zwart + Champagne		380-44	914161BM0
3 luminaires no slots 220-240VAC always use with hooks	Zwart + brons		380-44	914161BQ0
3 luminaires no slots 220-240VAC always use with hooks	Wit		380-44	914161WW0
6 luminaires no slots 220-240VAC always use with hooks	Zwart		380-44	914162BB0
6 luminaires no slots 220-240VAC always use with hooks	Zwart + Aluminium		380-44	914162BL0
6 luminaires no slots 220-240VAC always use with hooks	Zwart + Champagne		380-44	914162BM0
6 luminaires no slots 220-240VAC always use with hooks	Zwart + brons		380-44	914162BQ0
6 luminaires no slots 220-240VAC always use with hooks	Wit		380-44	914162WW0
9 luminaires no slots 220-240VAC always use with hooks	Zwart		380-44	914163BB0
9 luminaires no slots 220-240VAC always use with hooks	Zwart + Aluminium		380-44	914163BL0
9 luminaires no slots 220-240VAC always use with hooks	Zwart + Champagne		380-44	914163BM0
9 luminaires no slots 220-240VAC always use with hooks	Zwart + brons		380-44	914163BQ0
9 luminaires no slots 220-240VAC always use with hooks	Wit		380-44	914163WW0

TRACK ACCESSOIRES
TRACKADAPTER

TYPE	KLEUR	SPANNING	L-H (MM)	ARTIKEL NUMMER
3-phase track 220-240VAC	Zwart		158-46	914173B0
3-phase track 220-240VAC	Wit		158-46	914173W0