




PROJECT _____

TYPE _____

NOTES _____

QUANTITY _____

DATE _____



Ring shaped suspended luminaire made from die-cast aluminium; inclusive adjustable cable suspension max. 4000mm and base in Signal Black; surface Bronze; wet painted, matt smooth; silicone cover; PCB 3-step binning; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; 220 - 240 V; degree of protection IP20; Class 2; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;

GENERAL

Ceiling _____
 Suspended _____
 Bronze _____
 IP20 _____
 Interior _____
 1520 lm _____
 CIE flux code: 23 50 78 50 100 _____

LED

2700 K _____
 L80 / 100000h _____

OPTICAL


Opal _____

ELECTRICAL

phase-cut dim _____
 220 - 240 V _____
 system 18.8 W _____
 Class 2 _____

PHYSICAL

diameter 756 mm _____
 height 25 mm _____
 1,05 kg _____



[271382Q3] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.98	0.96	0.94	0.93	0.91
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.