



PROJECT

---

TYPE

---

NOTES

---

QUANTITY

---

DATE

---



**GENERAL**

Ceiling \_\_\_\_\_  
 Surface \_\_\_\_\_  
 White Matt + Black Matt \_\_\_\_\_  
 IP20 \_\_\_\_\_  
 Interior \_\_\_\_\_  
 440 lm \_\_\_\_\_

**LED**

2700 K \_\_\_\_\_  
 CRI  $\geq$  90 \_\_\_\_\_  
 initial MacAdam  $\leq$  2 SDCM \_\_\_\_\_  
 initial MacAdam  $\leq$  2 SDCM \_\_\_\_\_

**OPTICAL**

Standard \_\_\_\_\_  
 beam angle 30° \_\_\_\_\_


**ELECTRICAL**

phase-cut dim \_\_\_\_\_  
 220 - 240 V \_\_\_\_\_  
 system 8.0 W \_\_\_\_\_  
 Class 1 \_\_\_\_\_

**PHYSICAL**

diameter 70 mm \_\_\_\_\_  
 height 85 mm \_\_\_\_\_  
 0.19 kg \_\_\_\_\_

Cylindrical ceiling surface mounted downlight made from die-cast aluminium; surface White Matt + Black Matt; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam  $\leq$  2 SDCM; CRI  $\geq$  90; beam angle 30°; degree of protection IP20; Class 1; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;



[‘258254WB3’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.