



**PROJECT**  
\_\_\_\_\_

**TYPE**  
\_\_\_\_\_

**NOTES**  
\_\_\_\_\_

**QUANTITY**  
\_\_\_\_\_

**DATE**  
\_\_\_\_\_



**GENERAL**

Ceiling  
Surface  
Champagne + Black Matt  
IP20  
Interior

**LED**

3000 K  
CRI ≥ 90  
initial MacAdam ≤ 2 SDCM  
initial MacAdam ≤ 2 SDCM

**OPTICAL**

Standard  
beam angle 25°

**ELECTRICAL**


phase-cut dim  
220 - 240 V  
10.0 W  
Class 1

**PHYSICAL**

diameter 70 mm  
height 85 mm  
0.19 kg



Cylindrical ceiling surface mounted downlight made from die-cast aluminium; surface Champagne + Black Matt; max. 12W; 220 - 240 V; degree of protection IP20; Class 1; optional inner reflector available; lamp not included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;



[‘258254MB5’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.