



PROJECT

TYPE

NOTES

QUANTITY

DATE



Cylindrical ceiling surface mounted downlight made from die-cast aluminium; surface Black Matt + Bronze; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; beam angle 30°; degree of protection IP20; Class 1; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;

GENERAL

Ceiling
 Surface
 Black Matt + Bronze
 IP20
 Interior
 470 lm

LED

3000 K
 CRI ≥ 90
 initial MacAdam ≤ 2 SDCM
 initial MacAdam ≤ 2 SDCM

OPTICAL


Standard
 beam angle 30°

ELECTRICAL

phase-cut dim
 220 - 240 V
 system 8.0 W
 Class 1

PHYSICAL

diameter 70 mm
 height 85 mm
 0.19 kg



[‘258254BQ5’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.