




**PROJECT**

**TYPE**

**NOTES**

**QUANTITY**

**DATE**



Ceiling surface luminaire with 1 spotlight; made from die-cast aluminium; surface Black Matt; powder coated, matt texture; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; binning initial MacAdam  $\leq 2$  SDCM; CRI  $\geq 90$ ; beam angle 31°; spotlight head 350° rotatable and 90° tiltable; degree of protection IP20; Class 1; driver included; optional optical accessories available; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;

**GENERAL**

Ceiling  
Surface  
tilt max 90 °  
rotation 350 °  
Black Matt  
IP20  
Interior  
585 lm  
CIE flux code: 93 98 100 100  
100

**LED**

2700 K  
CRI  $\geq 90$   
L80 / 50000 h  
initial MacAdam  $\leq 2$  SDCM

**OPTICAL**


Standard  
beam angle 31°

**ELECTRICAL**

phase-cut dim  
220 - 240 V  
system 7.9 W  
Class 1

**PHYSICAL**

diameter 32 mm  
height 55 mm  
0.4 kg





## Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.96	0.92	0.88	0.85	0.81
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

<sup>a</sup>According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## OPTICAL ACCESSORIES

### Honeycomb Louver

Type	Colour	Ø (MM)	Item number
BLIEK PETIT   CENO   LECA   PIRRO	Black	29	90051131