

181684LS3




PROJECT

TYPE

NOTES

QUANTITY

DATE












Round shape wall surface mounted luminaire with diffuse light; aluminium base in White Matt wet painted; matt texture; aluminium shade; surface Live Simple wet painted; matt texture; RAL 090 9005; white opal glass handblown; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam \leq 2 SDCM; CRI \geq 90; CRI (Colour Rendering Index) \geq 90; degree of protection IP20; Class 1; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;



GENERAL

Wall
Surface
Live Simple
RAL 090 9005 ^a
IP20
Interior
465 lm
CIE flux code: 18 43 71 50 100

LED

2700 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM

OPTICAL

Opal

ELECTRICAL

phase-cut dim
220 - 240 V
system 10.1 W
Class 1

PHYSICAL

diameter 700 mm
height 94 mm
2.09 kg

^a Colour may deviate slightly due to production conditions.



181684LS3



Maintenance Factor

LLMF 0.96 0.92 0.88 0.85	Operating Time [h]	10.000	20.000	30.000	40.000	50.000
1 1 1 1	LLMF	0.96	0.92	0.88	0.85	0.81
	LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.