




PROJECT _____

TYPE _____


NOTES _____

QUANTITY _____

DATE _____



Cylindrical wall surface mounted luminaire made from aluminium; surface Champagne; direct/indirect light distribution; PCB 3-step binning; light colour 1800 K - 3000 K colour warm dimming; CRI \geq 90; 24 V; degree of protection IP20; Class 3; driver included; inclusive flaps for adjustable beam angle; light source replaceable by an authorized professional;



GENERAL

Wall _____
 Surface _____
 Champagne _____
 IP20 _____
 Interior _____
 total 900 lm _____

LED

colour warm dimming _____
 1800 K - 3000 K _____
 CRI \geq 90 _____
 initial MacAdam \leq 3 SDCM _____

OPTICAL

Variable _____

ELECTRICAL

excl. power supply _____
 24 V _____
 system 15.0 W _____
 Class 3 _____

PHYSICAL

diameter 150 mm _____
 height 160 mm _____
 1,07 kg _____

[‘34224LM9’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.