



PROJECT

---

TYPE

---

NOTES


---

QUANTITY


---

DATE

---



Cylindrical wall surface mounted luminaire made from aluminium; surface White Matt; powder coated; matt texture; direct/indirect light distribution; PCB 3-step binning; light colour 1800 K - 3000 K colour warm dimming; CRI  $\geq$  90; 24 V; degree of protection IP20; Class 3; driver included; inclusive flaps for adjustable beam angle; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



**GENERAL**

Wall \_\_\_\_\_  
 Surface \_\_\_\_\_  
 White Matt \_\_\_\_\_  
 IP20 \_\_\_\_\_  
 Interior \_\_\_\_\_  
 total 900 lm \_\_\_\_\_

**LED**

colour warm dimming \_\_\_\_\_  
 1800 K - 3000 K \_\_\_\_\_  
 CRI  $\geq$  90 \_\_\_\_\_  
 initial MacAdam  $\leq$  3 SDCM \_\_\_\_\_

**OPTICAL**

Variable \_\_\_\_\_

**ELECTRICAL**

excl. power supply \_\_\_\_\_  
 24 V \_\_\_\_\_  
 system 15.0 W \_\_\_\_\_  
 Class 3 \_\_\_\_\_

**PHYSICAL**

diameter 150 mm \_\_\_\_\_  
 height 100 mm \_\_\_\_\_  
 0.86 kg \_\_\_\_\_