




**PROJECT** \_\_\_\_\_

**TYPE** \_\_\_\_\_


**NOTES** \_\_\_\_\_

**QUANTITY** \_\_\_\_\_

**DATE** \_\_\_\_\_



Cylindrical wall surface mounted luminaire made from aluminium; surface Copper; wet painted; brushed; direct/indirect light distribution; PCB 3-step binning; light colour 1800 K - 3000 K colour warm dimming; CRI ≥ 90; 24 V; degree of protection IP20; Class 3; driver included; inclusive flaps for adjustable beam angle; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



**GENERAL**

Wall \_\_\_\_\_  
 Surface \_\_\_\_\_  
 Copper \_\_\_\_\_  
 IP20 \_\_\_\_\_  
 Interior \_\_\_\_\_  
 total 900 lm \_\_\_\_\_

**LED**

colour warm dimming \_\_\_\_\_  
 1800 K - 3000 K \_\_\_\_\_  
 CRI ≥ 90 \_\_\_\_\_  
 initial MacAdam ≤ 3 SDCM \_\_\_\_\_

**OPTICAL**

Variable \_\_\_\_\_

**ELECTRICAL**

excl. power supply \_\_\_\_\_  
 24 V \_\_\_\_\_  
 system 15.0 W \_\_\_\_\_  
 Class 3 \_\_\_\_\_

**PHYSICAL**

diameter 150 mm \_\_\_\_\_  
 height 100 mm \_\_\_\_\_  
 0.86 kg \_\_\_\_\_

[“34214LP9”] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.