




PROJECT

TYPE


NOTES

QUANTITY

DATE



Cylindrical wall surface mounted luminaire made from aluminium; surface Aluminium Brushed; direct/indirect light distribution; PCB 3-step binning; light colour 1800 K - 3000 K colour warm dimming; CRI ≥ 90 ; 24 V; degree of protection IP20; Class 3; driver included; inclusive flaps for adjustable beam angle; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



GENERAL

Wall
 Surface
 Aluminium Brushed
 IP20
 Interior
 total 900 lm

LED

colour warm dimming
 1800 K - 3000 K
 CRI ≥ 90
 initial MacAdam ≤ 3 SDCM

OPTICAL

Variable

ELECTRICAL

excl. power supply
 24 V
 system 15.0 W
 Class 3

PHYSICAL

diameter 150 mm
 height 100 mm
 0.86 kg

[‘34214LL9’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.