



PROJECT

TYPE

NOTES

QUANTITY

DATE



GENERAL

Ceiling _____
 Surface _____
 White Matt _____
 IP20 _____
 Interior _____
 450 lm _____

LED

colour warm dimming _____
 1800 K - 3000 K _____
 CRI \geq 90 _____
 initial MacAdam \leq 2 SDCM _____

OPTICAL

beam angle 38° _____

ELECTRICAL


excl. power supply _____
 24 V _____
 system 7.0 W _____
 Class 3 _____

PHYSICAL

diameter 70 mm _____
 height 82 mm _____
 0.24 kg _____



Cylindrical ceiling surface mounted downlight made from die-cast aluminium; surface White Matt; powder coated; matt texture; with COB (Chip on Board) technology for maximum efficiency; light colour 1800 K - 3000 K colour warm dimming; CRI \geq 90; beam angle 38°; degree of protection IP20; Class 3; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



[25825LWW9] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.