



PROJECT

TYPE

NOTES

QUANTITY

DATE



Cylindrical ceiling suspended luminaire made from die-cast aluminium; surface White Matt; powder coated; matt texture; inclusive adjustable cable suspension max. 4000mm in Pure White; with COB (Chip on Board) technology for maximum efficiency; light colour 1800 K - 3000 K colour warm dimming; CRI ≥ 90; 24 V; degree of protection IP20; Class 3; driver included; ceiling base included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

GENERAL

Ceiling
Suspended
White Matt
IP20
Interior
570 lm

LED

colour warm dimming
1800 K - 3000 K
CRI ≥ 90
initial MacAdam ≤ 2 SDCM

OPTICAL


Standard
beam angle 36°

ELECTRICAL

excl. power supply
24 V
system 7.0 W
Class 3

PHYSICAL

diameter 67 mm
height 300 mm
0.76 kg



[‘22686LW9’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.