



PROJECT

---

TYPE

---

NOTES

---

QUANTITY

---

DATE

---



Cylindrical ceiling suspended luminaire made from die-cast aluminium; surface Aluminium Brushed; inclusive adjustable cable suspension max. 4000mm in Signal Black; with COB (Chip on Board) technology for maximum efficiency; light colour 1800 K - 3000 K colour warm dimming; CRI ≥ 90; 24 V; degree of protection IP20; Class 3; driver included; ceiling base included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

**GENERAL**

Ceiling  
Suspended  
Aluminium Brushed  
IP20  
Interior  
570 lm

**LED**

colour warm dimming  
1800 K - 3000 K  
CRI ≥ 90  
initial MacAdam ≤ 2 SDCM

**OPTICAL**


Standard  
beam angle 36°

**ELECTRICAL**

excl. power supply  
24 V  
system 7.0 W  
Class 3

**PHYSICAL**

diameter 67 mm  
height 300 mm  
0.76 kg



[22686LL9] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.