



WEVER & DUCRÉ  
LIGHTING

# RAY SUSPENDED 2.0 Loxone

22676LP9

Project \_\_\_\_\_

Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantity \_\_\_\_\_

Date \_\_\_\_\_

## GENERAL

Ceiling , Suspended \_\_\_\_\_

Copper \_\_\_\_\_

IP20 \_\_\_\_\_

Interior \_\_\_\_\_

Output: 570 lm \_\_\_\_\_

## LED

colour warm dimming \_\_\_\_\_

1800 K - 3000 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

2 SDCM \_\_\_\_\_

## OPTICAL

Standard , Beam angle 36° \_\_\_\_\_

## ELECTRICAL

excl. power supply \_\_\_\_\_

24 V \_\_\_\_\_

Total connected power 7.0 W \_\_\_\_\_

Class 3 \_\_\_\_\_

## PHYSICAL

Diameter 67 mm \_\_\_\_\_

Height 200 mm \_\_\_\_\_

0.62 kg \_\_\_\_\_



Cylindrical ceiling suspended luminaire made from die-cast aluminium; surface Copper; wet painted; brushed; inclusive adjustable cable suspension max. 4000mm in Signal Black; ceiling base not included; light source replaceable by Wever Ducré or by a professional with explicit authorization;

