



**PROJECT** \_\_\_\_\_

**TYPE** \_\_\_\_\_

**NOTES** \_\_\_\_\_

**QUANTITY** \_\_\_\_\_

**DATE** \_\_\_\_\_



**GENERAL**

Ceiling \_\_\_\_\_

Suspended \_\_\_\_\_

Copper \_\_\_\_\_

IP20 \_\_\_\_\_

Interior \_\_\_\_\_

570 lm \_\_\_\_\_

**LED**

colour warm dimming \_\_\_\_\_

1800 K - 3000 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

initial MacAdam ≤ 2 SDCM \_\_\_\_\_

**OPTICAL**

Standard \_\_\_\_\_

beam angle 36° \_\_\_\_\_

**ELECTRICAL**

excl. power supply \_\_\_\_\_

24 V \_\_\_\_\_

system 7.0 W \_\_\_\_\_

Class 3 \_\_\_\_\_

**PHYSICAL**


diameter 67 mm \_\_\_\_\_

height 200 mm \_\_\_\_\_

0.62 kg \_\_\_\_\_



Cylindrical ceiling suspended luminaire made from die-cast aluminium; surface Copper; wet painted; brushed; inclusive adjustable cable suspension max. 4000mm in Signal Black; with COB (Chip on Board) technology for maximum efficiency; light colour 1800 K - 3000 K colour warm dimming; CRI ≥ 90; 24 V; degree of protection IP20; Class 3; driver included; ceiling base included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



[‘22676LP9’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.