



PROJECT

TYPE

NOTES

QUANTITY

DATE



GENERAL

Ceiling _____
 Suspended _____
 Champagne _____
 IP20 _____
 Interior _____
 570 lm _____

LED

colour warm dimming _____
 1800 K - 3000 K _____
 CRI ≥ 90 _____
 initial MacAdam ≤ 2 SDCM _____

OPTICAL

Standard _____
 beam angle 36° _____

ELECTRICAL


excl. power supply _____
 24 V _____
 system 7.0 W _____
 Class 3 _____

PHYSICAL

diameter 67 mm _____
 height 200 mm _____
 0.62 kg _____



Cylindrical ceiling suspended luminaire made from die-cast aluminium; surface Champagne; inclusive adjustable cable suspension max. 4000mm in Signal Black; with COB (Chip on Board) technology for maximum efficiency; light colour 1800 K - 3000 K colour warm dimming; CRI ≥ 90; 24 V; degree of protection IP20; Class 3; driver included; ceiling base included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



[‘22676LM9’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.