




PROJECT _____

TYPE _____

NOTES _____

QUANTITY _____

DATE _____



Round ceiling recessed downlight made from die-cast aluminium; adjustable; surface Black Matt + Gold; wet painted, matt smooth; inner ring black; installation without tools using blade springs; with COB (Chip on Board) technology for maximum efficiency; light colour 1800 K - 3000 K colour warm dimming; CRI ≥ 90; beam angle 38°; 355° rotatable and 60° tiltable; degree of protection IP20; Class 3; IC rated; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

GENERAL

Ceiling _____
 Recessed _____
 tilt max 60 ° _____
 rotation 355 ° _____
 Black Matt + Gold _____
 IP20 _____
 Interior _____
 500 lm _____

LED

colour warm dimming _____
 1800 K - 3000 K _____
 CRI ≥ 90 _____
 initial MacAdam ≤ 2 SDCM _____

OPTICAL

Standard _____
 beam angle 38° _____

ELECTRICAL

excl. power supply _____
 24 V _____
 system 7.0 W _____
 Class 3 _____

PHYSICAL

diameter 62 mm _____
 height 96 mm _____
 0.45 kg _____
 blade springs _____



[12536LBG9C] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.