



PROJECT

---

TYPE

---

NOTES

---

QUANTITY

---

DATE

---



**GENERAL**

Ceiling \_\_\_\_\_  
 Recessed \_\_\_\_\_  
 tilt max 60 ° \_\_\_\_\_  
 rotation 355 ° \_\_\_\_\_  
 Black Matt \_\_\_\_\_  
 IP20 \_\_\_\_\_  
 Interior \_\_\_\_\_  
 500 lm \_\_\_\_\_

**LED**

colour warm dimming \_\_\_\_\_  
 1800 K - 3000 K \_\_\_\_\_  
 CRI ≥ 90 \_\_\_\_\_  
 initial MacAdam ≤ 2 SDCM \_\_\_\_\_

**OPTICAL**


Standard \_\_\_\_\_  
 beam angle 38° \_\_\_\_\_

**ELECTRICAL**

excl. power supply \_\_\_\_\_  
 24 V \_\_\_\_\_  
 system 7.0 W \_\_\_\_\_  
 Class 3 \_\_\_\_\_

**PHYSICAL**

diameter 62 mm \_\_\_\_\_  
 height 96 mm \_\_\_\_\_  
 0.45 kg \_\_\_\_\_  
 wire springs \_\_\_\_\_



Round ceiling recessed downlight made from die-cast aluminium; adjustable; surface Black Matt; powder coated, matt texture; inner ring black; installation without tools using wire springs; with COB (Chip on Board) technology for maximum efficiency; light colour 1800 K - 3000 K colour warm dimming; CRI ≥ 90; beam angle 38°; 355° rotatable and 60° tiltable; degree of protection IP20; Class 3; IC rated; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



[12536LBB9] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.