



PROJECT

---

TYPE

---

NOTES

---

QUANTITY

---

DATE

---



Table luminaire made from aluminium; surface Black Matt; powder coated; matt texture; magnetic pole with optional base; rechargeable lithium-ion battery inclusive 1500mm USB charging cable; lights up to 8 hours; touch dim; light colour 2700 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 80$ ; degree of protection IP23; fixation accessories with or without charging function available;

## GENERAL

Table  
Standing  
Black Matt  
RAL 9005 <sup>a</sup>  
IP23  
Interior  
135 lm  
CIE flux code: 48 79 95 98 100

## LED

2700 K  
CRI  $\geq 80$   
L80 / 60000 h  
initial MacAdam  $\leq 3$  SDCM

## OPTICAL

Opal

## ELECTRICAL

touch dim  
1.8 W

## PHYSICAL

length 116 mm  
width 116 mm  
height 308 mm  
0.8 kg

<sup>a</sup> Colour may deviate slightly due to production conditions.





**Maintenance Factor**

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.97	0.93	0.89	0.86	0.82
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

<sup>a</sup>According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

**BASE**

**Charging Tray**

Type	Colour	L·W·H (MM)	Item number
REVER DINING	White	180-135-1,3	90019165
REVER DINING	Black	180-135-1,3	90019166
REVER DINING	Bronze	180-135-1,3	90019175

**Magnetic Flat Plate**

Type	Colour	L·W·H (MM)	Item number
REVER DINING	White	180-135-1,5	90019163
REVER DINING	Black	180-135-1,5	90019164

**Multiple Charging Tray**

Type	Item number
REVER DINING	90018007

[655184B2] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.