



**PROJECT** \_\_\_\_\_

**TYPE** \_\_\_\_\_

**NOTES** \_\_\_\_\_

**QUANTITY** \_\_\_\_\_

**DATE** \_\_\_\_\_



**GENERAL**

Wall \_\_\_\_\_  
 Surface \_\_\_\_\_  
 Bronze \_\_\_\_\_  
 IP20 \_\_\_\_\_  
 Interior \_\_\_\_\_  
 total 440 lm \_\_\_\_\_

**LED**

3000 K \_\_\_\_\_  
 CRI  $\geq$  90 \_\_\_\_\_  
 initial MacAdam  $\leq$  3 SDCM \_\_\_\_\_

**OPTICAL**

Variable \_\_\_\_\_

**ELECTRICAL**


phase-cut dim \_\_\_\_\_  
 220 - 240 V \_\_\_\_\_  
 6.0 W \_\_\_\_\_  
 Class 1 \_\_\_\_\_

**PHYSICAL**

diameter 150 mm \_\_\_\_\_  
 height 160 mm \_\_\_\_\_  
 0.85 kg \_\_\_\_\_



Cylindrical wall surface mounted luminaire made from aluminium; surface Bronze; wet painted; brushed; direct/indirect light distribution; PCB 3-step binning; phase-cut dim; light colour 3000 K; binning initial MacAdam  $\leq$  3 SDCM; CRI  $\geq$  90; 220 - 240 V; degree of protection IP20; Class 1; inclusive flaps for adjustable beam angle;



[‘332248Q4’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.