



PROJECT _____

TYPE _____

NOTES _____

QUANTITY _____

DATE _____



GENERAL

Wall _____
 Surface _____
 Copper _____
 IP20 _____
 Interior _____
 total 400 lm _____

LED

colour warm dimming _____
 1800 K - 2850 K _____
 CRI \geq 90 _____

OPTICAL

Variable _____

ELECTRICAL


phase-cut dim _____
 220 - 240 V _____
 system 6.0 W _____
 Class 1 _____

PHYSICAL

diameter 150 mm _____
 height 150 mm _____
 0.85 kg _____



Cylindrical wall surface mounted luminaire made from aluminium; surface Copper; wet painted; brushed; direct/indirect light distribution; PCB 3-step binning; phase-cut dim; light colour 1800 K - 2850 K colour warm dimming; CRI \geq 90; 220 - 240 V; degree of protection IP20; Class 1; driver included; inclusive flaps for adjustable beam angle;



[‘332248P9’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.