



**PROJECT** \_\_\_\_\_

**TYPE** \_\_\_\_\_


**NOTES** \_\_\_\_\_

**QUANTITY** \_\_\_\_\_

**DATE** \_\_\_\_\_



Cylindrical wall surface mounted luminaire made from aluminium; surface Black Matt; powder coated; matt texture; RAL 9005; direct/indirect light distribution; PCB 3-step binning; phase-cut dim; light colour 1800 K - 2850 K colour warm dimming; CRI ≥ 90; 220 - 240 V; degree of protection IP20; Class 1; driver included; inclusive flaps for adjustable beam angle;



**GENERAL**

Wall \_\_\_\_\_

Surface \_\_\_\_\_

Black Matt \_\_\_\_\_

RAL 9005 <sup>a</sup> \_\_\_\_\_

IP20 \_\_\_\_\_

Interior \_\_\_\_\_

total 400 lm \_\_\_\_\_

**LED**

colour warm dimming \_\_\_\_\_

1800 K - 2850 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

**OPTICAL**

Variable \_\_\_\_\_

**ELECTRICAL**

phase-cut dim \_\_\_\_\_

220 - 240 V \_\_\_\_\_

system 6.0 W \_\_\_\_\_

Class 1 \_\_\_\_\_

**PHYSICAL**

diameter 150 mm \_\_\_\_\_

height 150 mm \_\_\_\_\_

0.85 kg \_\_\_\_\_

<sup>a</sup> Colour may deviate slightly due to production conditions.