



PROJECT

TYPE

NOTES

QUANTITY

DATE



Cylindrical wall surface mounted luminaire made from aluminium; surface White Matt; powder coated; matt texture; RAL 9010; direct light distribution; PCB 3-step binning; phase-cut dim; light colour 1800 K - 2850 K colour warm dimming; CRI \geq 90; 220 - 240 V; degree of protection IP20; Class 1; inclusive flaps for adjustable beam angle;

GENERAL

Wall _____
 Surface _____
 White Matt _____
 RAL 9010 ^a _____
 IP20 _____
 Interior _____
 400 lm _____

LED

colour warm dimming _____
 1800 K - 2850 K _____
 CRI \geq 90 _____

OPTICAL

Variable _____


ELECTRICAL

phase-cut dim _____
 220 - 240 V _____
 system 6.0 W _____
 Class 1 _____

PHYSICAL

diameter 150 mm _____
 height 100 mm _____
 0.62 kg _____

^a Colour may deviate slightly due to production conditions.



[‘332168W9’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.