

RAY WALL 2.0 LED

332148W9



| PROJECT | | |
|----------|--|--|
| ТҮРЕ | | |
| NOTES | | |
| QUANTITY | | |
| DATE | | |





Cylindrical wall surface mounted luminaire made from aluminium; surface White Matt; powder coated; matt texture; RAL 9010; direct/ indirect light distribution; PCB 3-step binning; phase-cut dim; light colour 1800 K - 2850 K colour warm dimming; CRI \geq 90; 220 - 240 V; degree of protection IP20; Class 1; driver included; inclusive flaps for adjustable beam angle;



| Wall |
|-----------------------|
| Surface |
| White Matt |
| RAL 9010 ^a |
| IP20 |
| Interior |
| total 400 lm |
| |

LED

colour warm dimming 1800 K - 2850 K $CRI \ge 90$

OPTICAL

Variable

ELECTRICAL

| phase-cut dim | |
|---------------|--|
| 220 - 240 V | |
| system 6.0 W | |
| Class 1 | |
| | |

PHYSICAL

| diameter 150 mm | |
|-----------------|--|
| height 100 mm | |
| 0.69 kg | |

^a Colour may deviate slightly due to production conditions.



['332148W9'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply. © Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com