



**PROJECT** \_\_\_\_\_

**TYPE** \_\_\_\_\_

**NOTES** \_\_\_\_\_

**QUANTITY** \_\_\_\_\_

**DATE** \_\_\_\_\_



Tubular wall surface luminaire made from aluminium; surface Black Matt; powder coated; matt texture; RAL 9005; cable plug with switch in black; phase-cut dim; light colour 3000 K; CRI ≥ 90; 220 - 240 V; degree of protection IP20; Class 2; light source replaceable by end-user;

**GENERAL**

Wall \_\_\_\_\_  
 Surface \_\_\_\_\_  
 Black Matt \_\_\_\_\_  
 RAL 9005 <sup>a</sup> \_\_\_\_\_  
 IP20 \_\_\_\_\_  
 Interior \_\_\_\_\_  
 2940 lm \_\_\_\_\_  
 CIE flux code: 40 70 89 90 100 \_\_\_\_\_

**LED**

3000 K \_\_\_\_\_  
 CRI ≥ 90 \_\_\_\_\_  
 L70 / 50000h \_\_\_\_\_  
 initial MacAdam ≤ 3 SDCM \_\_\_\_\_

**OPTICAL**

Opal \_\_\_\_\_

**ELECTRICAL**

phase-cut dim \_\_\_\_\_  
 220 - 240 V \_\_\_\_\_  
 system 23.0 W \_\_\_\_\_  
 Class 2 \_\_\_\_\_

**PHYSICAL**

length 33 mm \_\_\_\_\_  
 width 1626 mm \_\_\_\_\_  
 height 33 mm \_\_\_\_\_  
 0.33 kg \_\_\_\_\_  
 cable plug with switch \_\_\_\_\_

<sup>a</sup> Colour may deviate slightly due to production conditions.

