



PROJECT

TYPE

NOTES

QUANTITY

DATE



Tubular wall surface luminaire made from aluminium; surface Black Matt; powder coated; matt texture; RAL 9005; cable plug with switch in black; non dim; light colour 4000 K; CRI ≥ 80; 220 - 240 V; degree of protection IP20; Class 2; light source replaceable by end-user;

GENERAL

Wall _____
 Surface _____
 Black Matt _____
 RAL 9005 ^a _____
 IP20 _____
 Interior _____
 3950 lm _____
 CIE flux code: 36 64 84 71 100 _____

LED

4000 K _____
 CRI ≥ 80 _____
 L70 / 60000h _____
 initial MacAdam ≤ 3 SDCM _____

OPTICAL

Opal _____


ELECTRICAL

non dim _____
 220 - 240 V _____
 system 22.1 W _____
 Class 2 _____

PHYSICAL

length 33 mm _____
 width 1626 mm _____
 height 33 mm _____
 0.33 kg _____
 cable plug with switch _____

^a Colour may deviate slightly due to production conditions.



[‘2563T7B6’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.