



WEVER & DUCRÉ
LIGHTING

FINLIN 3.0

370384B5

Project

Type

Notes

Quantity

Date

GENERAL

Wall
Surface
Jet Black
RAL 9005^a
Below IP20
Interior
680 lm

LED

3000 K
CRI \geq 90
L80 B50 / 60000h
3-step binning


ELECTRICAL

phase-cut dim
220 - 240 V
LED Inset 7 W
Class 2
Safety distance 0.3 m


PHYSICAL

Length 9 mm
Width 7 mm
Height 1239 mm
0.3 kg


^a Color may deviate slightly due to production conditions.



Wall surface luminaire made from aluminium; surface Jet Black; powder coated; matt texture; RAL 9005; opal PMMA diffuser; PCB 3-step binning; phase-cut dim; light colour 3000 K; binning initial MacAdam 3 SDCM; CRI 90; CRI (Colour Rendering Index) 90; 220 - 240 V; degree of protection IP20; PC2; driver included; light source replaceable by an authorized professional; control gear replaceable by end-user;



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

FINLIN 3.0

370384B5

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.96	0.93	0.89	0.86	0.83
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.