



WEVER & DUCRÉ  
LIGHTING

# RAY

## mini 1.0 PAR16

258220W0

Project

Type

Notes

Quantity

Date

### GENERAL

Ceiling, Surface

White Matt

RAL 9003<sup>a</sup>

IP20

Interior

Output: 365<sup>b</sup>, 480<sup>c</sup>, 520<sup>d</sup> lm

CIE flux code: 94 98 100 100 95

### LED

Lamp PAR16

Socket GU10

max. per socket 12.0 W

CRI ≥ 80 to 90

### ELECTRICAL

100 - 240 V

LED Inset 4.4<sup>b</sup> to 6.5<sup>c,d</sup> W

Class 1

### PHYSICAL

Diameter 70 mm

Height 82 mm

0.14 kg

<sup>a</sup> Color may deviate slightly due to production conditions.


<sup>b</sup> PAR16 LAMP 2700K CRI80

<sup>c</sup> PAR16 LAMP 2700K CRI90


<sup>d</sup> PAR16 LAMP 3000K CRI90



Cylindrical ceiling surface mounted downlight made from die-cast aluminium; surface White Matt; powder coated; matt texture; RAL 9003; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; degree of protection IP20; Class 1; UGR ≤ 19; optional inner reflector available; lamp not included;



### LIGHT DISTRIBUTION



RAY

mini 1.0 PAR16

258220W0

LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
2700K   >90 CRI   GU10	Black	ø50-60	9 0 1 2 2 8 B 3
3000K   >90 CRI   GU10	Black	ø50-60	9 0 1 2 2 8 B 5
2700K   >90 CRI   GU10	White	ø50-60	9 0 1 2 2 8 W 3
3000K   >90 CRI   GU10	White	ø50-60	9 0 1 2 2 8 W 5
2700K   >80 CRI   GU10	Silver	ø50-60	9 0 5 2 2 7 S 2
3000K   >80 CRI   GU10	Silver	ø50-60	9 0 5 2 2 7 S 4

OPTICAL

Inner Reflector

TYPE	COLOUR	ORDERCODE
RAY mini   max. 10W	Black	9 0 0 1 9 9 B 4
RAY mini   max. 10W	Gold	9 0 0 1 9 9 G 4
RAY mini   max. 10W	Champagne	9 0 0 1 9 9 M 4
RAY mini   max. 10W	Bronze	9 0 0 1 9 9 Q 4
RAY mini   max. 10W	White	9 0 0 1 9 9 W 4