



WEVER & DUCRÉ
LIGHTING

RAY

mini 1.0 PAR16

258220Q0 900199G4

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling, Surface

Bronze

Gold

IP20

Interior

Output: 360^a, 430^b, 450^c lm

CIE flux code: 94 98 100 100 93

LED

Lamp PAR16

Socket GU10

max. per socket 12.0 W

CRI ≥ 80 to 90

ELECTRICAL

100 - 240 V

LED Inset 4.4^a to 6.5^{cb} W

Class 1

PHYSICAL

Diameter 70 mm

Height 82 mm

0.14 kg


^a PAR16 LAMP 2700K CRI80, inner reflector gold

^b PAR16 LAMP 2700K CRI90, inner reflector gold


^c PAR16 LAMP 3000K CRI90, inner reflector gold



Cylindrical ceiling surface mounted downlight made from die-cast aluminium; surface Bronze; wet painted; brushed; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; degree of protection IP20; Class 1; UGR ≤ 19; inclusive single inner reflector in Gold; lamp not included;



LIGHT DISTRIBUTION



RAY

mini 1.0 PAR16

258220Q0 900199G4

COMPONENTS

Inner Reflector

TYPE	ORDERCODE
RAY mini max. 10W	9 0 0 1 9 9 G 4

LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
2700K >90 CRI GU10	Black	Ø50 · 60	9 0 1 2 2 8 B 3
3000K >90 CRI GU10	Black	Ø50 · 60	9 0 1 2 2 8 B 5
2700K >90 CRI GU10	White	Ø50 · 60	9 0 1 2 2 8 W 3
3000K >90 CRI GU10	White	Ø50 · 60	9 0 1 2 2 8 W 5
2700K >80 CRI GU10	Silver	Ø50 · 60	9 0 5 2 2 7 S 2
3000K >80 CRI GU10	Silver	Ø50 · 60	9 0 5 2 2 7 S 4