

# RAY

## mini 1.0 PAR16

258220B0 900199B4

### GENERAL

Ceiling , Surface

Black Matt

Black

RAL 9005 <sup>a</sup>

IP20

Interior

Output: 355<sup>b</sup>, 420<sup>c</sup>, 440<sup>d</sup> lm

CIE flux code: 94 98 100 100 92

### LED

Lamp PAR16

Socket GU10

max. per socket 12.0 W

CRI ≥ 80 to 90

### ELECTRICAL

100 - 240 V

LED Inset 4.4<sup>b</sup> to 6.5<sup>dc</sup> W

Class 1

### PHYSICAL

Diameter 70 mm

Height 82 mm

0.14 kg

<sup>a</sup> Color may deviate slightly due to production conditions.

<sup>b</sup> PAR16 LAMP 2700K CRI80, inner reflector black

<sup>c</sup> PAR16 LAMP 2700K CRI90, inner reflector black

<sup>d</sup> PAR16 LAMP 3000K CRI90, inner reflector black


Project

Type


Notes

Quantity


Date



Cylindrical ceiling surface mounted downlight made from die-cast aluminium; surface Black Matt; powder coated; matt texture; RAL 9005; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; degree of protection IP20; Class 1; UGR ≤ 19; inclusive single inner reflector in Black; lamp not included;



### LIGHT DISTRIBUTION



RAY

mini 1.0 PAR16

258220B0 900199B4

COMPONENTS

Inner Reflector

TYPE	ORDERCODE
RAY mini   max. 10W	9 0 0 1 9 9 B 4

LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
2700K   >90 CRI   GU10	Black	Ø50 · 60	9 0 1 2 2 8 B 3
3000K   >90 CRI   GU10	Black	Ø50 · 60	9 0 1 2 2 8 B 5
2700K   >90 CRI   GU10	White	Ø50 · 60	9 0 1 2 2 8 W 3
3000K   >90 CRI   GU10	White	Ø50 · 60	9 0 1 2 2 8 W 5
2700K   >80 CRI   GU10	Silver	Ø50 · 60	9 0 5 2 2 7 S 2
3000K   >80 CRI   GU10	Silver	Ø50 · 60	9 0 5 2 2 7 S 4