



151484K5



PROJECT

TYPE

NOTES

QUANTITY

DATE











Rectangular ceiling surface mounted downlight made from die-cast aluminium with opal PMMA cover; surface housing Black Matt powder coated; matt texture; with aesthetic frame in Gold wet painted; matt smooth; PCB 3-step binning; phase-cut dim; light colour 3000 K; binning initial MacAdam \leq 3 SDCM; CRI \geq 90; CRI (Colour Rendering Index) \geq 90; degree of protection IP20; Class 1; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;

GENERAL

Ceiling
Surface
Black Matt + Gold
RAL 9005 ^a
IP20
Interior
710 lm
CIE flux code: 65 94 100 100
100

LED

3000 K	
CRI ≥ 90	
L80 / 60000h	
initial MacAdam ≤ 3 SDCM	

OPTICAL

Opal


ELECTRICAL

phase-cut dim	
220 - 240 V	
system 12.0 W	
Class 1	
	_

PHYSICAL

length 182 mm	
width 50 mm	
height 65 mm	
0.52 kg	

^a Colour may deviate slightly due to production conditions.





151484K5



MOUNTING ACCESSORIES

4	^	C-:	1:	D
н.	·U	cei	ıına	Base

Туре	Colour	L·W·H (MM)	ltem number
PIRRO SYSTEM	White	754-51-12	90052072
PIRRO SYSTEM	Black	754-51-12	90052073
PIRRO SYSTEM	Gold	754:51:12	90052074

2.0 Ceiling Base

2.0 Cenning Base			
Туре	Colour	L·W·H (MM)	Item number
PIRRO SYSTEM	White	1150-51-12	90052075
PIRRO SYSTEM	Black	1150-51-12	90052076
PIRRO SYSTEM	Gold	1150-51-12	90052077