




PROJECT _____

TYPE _____

NOTES _____

QUANTITY _____

DATE _____



Cylindrical wall surface mounted luminaire made from aluminium; surface White Matt; powder coated; matt texture; RAL 9010; direct/indirect light distribution; PCB 3-step binning; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; 220 - 240 V; degree of protection IP20; Class 1; driver included; inclusive flaps for adjustable beam angle; light source replaceable by an authorized professional;

GENERAL

Wall _____
 Surface _____
 White Matt _____
 RAL 9010 ^a _____
 IP20 _____
 Interior _____
 total 690 lm _____
 CIE flux code: 71 92 98 50 100 _____

LED

3000 K _____
 CRI ≥ 90 _____
 initial MacAdam ≤ 3 SDCM _____

OPTICAL

Variable _____


ELECTRICAL

phase-cut dim _____
 220 - 240 V _____
 system 11.0 W _____
 Class 1 _____

PHYSICAL

diameter 150 mm _____
 height 160 mm _____
 0.85 kg _____

^a Colour may deviate slightly due to production conditions.



[‘342248W5’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.