



PROJECT

TYPE

NOTES

QUANTITY

DATE



GENERAL

Wall
 Surface
 Bronze
 IP20
 Interior
 total 620 lm

LED

colour warm dimming
 1800 K - 2850 K
 CRI \geq 90
 initial MacAdam \leq 3 SDCM

OPTICAL


Variable

ELECTRICAL


phase-cut dim
 220 - 240 V
 system 11.0 W
 Class 1

PHYSICAL

diameter 150 mm
 height 160 mm
 0.85 kg



Cylindrical wall surface mounted luminaire made from aluminium; surface Bronze; wet painted; brushed; direct/indirect light distribution; PCB 3-step binning; phase-cut dim; light colour 1800 K - 2850 K colour warm dimming; binning initial MacAdam \leq 3 SDCM; CRI \geq 90; 220 - 240 V; degree of protection IP20; Class 1; driver included; inclusive flaps for adjustable beam angle; light source replaceable by an authorized professional;



[‘342248Q9’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.