




**PROJECT** \_\_\_\_\_

**TYPE** \_\_\_\_\_

**NOTES** \_\_\_\_\_

**QUANTITY** \_\_\_\_\_

**DATE** \_\_\_\_\_



Cylindrical wall surface mounted luminaire made from aluminium; surface Aluminium Brushed; direct/indirect light distribution; PCB 3-step binning; phase-cut dim; light colour 2700 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; 220 - 240 V; degree of protection IP20; Class 1; driver included; inclusive flaps for adjustable beam angle; light source replaceable by an authorized professional;

**GENERAL**

Wall \_\_\_\_\_

Surface \_\_\_\_\_

Aluminium Brushed \_\_\_\_\_

IP20 \_\_\_\_\_

Interior \_\_\_\_\_

total 650 lm \_\_\_\_\_

CIE flux code: 71 92 98 50 100 \_\_\_\_\_

**LED**

2700 K \_\_\_\_\_

CRI  $\geq 90$  \_\_\_\_\_

initial MacAdam  $\leq 3$  SDCM \_\_\_\_\_

**OPTICAL**

Variable \_\_\_\_\_

**ELECTRICAL**

phase-cut dim \_\_\_\_\_

220 - 240 V \_\_\_\_\_

system 11.0 W \_\_\_\_\_

Class 1 \_\_\_\_\_

**PHYSICAL**

diameter 150 mm \_\_\_\_\_

height 160 mm \_\_\_\_\_

0.85 kg \_\_\_\_\_

