



PROJECT

TYPE

NOTES

QUANTITY

DATE



Cylindrical wall surface mounted luminaire made from aluminium; surface Black Matt; powder coated; matt texture; RAL 9005; direct/indirect light distribution; PCB 3-step binning; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; 220 - 240 V; degree of protection IP20; Class 1; driver included; inclusive flaps for adjustable beam angle; light source replaceable by an authorized professional;

GENERAL

Wall
 Surface
 Black Matt
 RAL 9005 ^a
 IP20
 Interior
 total 690 lm
 CIE flux code: 71 92 98 50 100

LED

3000 K
 CRI ≥ 90
 initial MacAdam ≤ 3 SDCM

OPTICAL

Variable


ELECTRICAL

phase-cut dim
 220 - 240 V
 system 11.0 W
 Class 1

PHYSICAL

diameter 150 mm
 height 160 mm
 0.85 kg

^a Colour may deviate slightly due to production conditions.



[‘342248B5’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.